

Product code: SFATA

The SFATA Telescopic Adaptor is used with the 450mm Pipe Riser chamber range to allow height & level adjustment for the cover and frame. It is suitable for direct connection to Polypipe 450mm Ductile Iron and Polypropylene covers & frames. The adaptor has an integral 350mm restrictor ring for non-man entry.



## Key Benefits

- Internal fit to RSW450X3PE8 riser
- Telescopic action allows up to 200mm of vertical adjustment and up to 7.5 degrees of lateral alignment (depending on insertion depth)
- Supplied with seal to internal face of the of riser and eye bolt fixings for securing to riser shaft internally
- Complete with integral restrictor ring to 350mm for non-man entry requirements
- Suitable for direct connection to UG510 cover & frame
- Suitable for use with Polypipe 450mm Ductile Iron covers and frames

## Installation Instructions

- Lubricate the finned gasket with Polypipe Joint Lubricant or Silicone Lubricant
- Position the SFATA Telescopic Adaptor inside the top of riser shaft and adjust to the correct height and level, fix using the four eye bolts provided.
- Height and alignment can be changed by removing the eye bolts and realigning the Telescopic Adaptor
- Position the cover and frame into the socket of the Telescopic Adaptor and secure with the appropriate fixings.