

## DECLARATION OF PERFORMANCE

Category 39 comprising of

Regency Red Multi  
Regency Orange Multi  
Regency Chesham Multi  
Tumbled Regency Multi Handmade

CAT 39 - RGY - 2020



**Group HD, Category II Handmade Clay Bricks**

Intended use or uses of the construction product, in accordance with with applicable harmonised technical specification, as foreseen by the manufacturer: **Facing clay masonry unit for internal or external use, load bearing or non load bearing masonry structures**

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION	
Dimensional Tolerances mm	65 x 215 x 102.5 68 x 228 x 108 (Regency Orange Multi, Regency Red Multi, Regency Chesham Multi ONLY)	BS EN771-1	
	Tolerance		T1
	Range		R1
Compressive Strength (Standard shape, tested normal to the bed face of the unit) N/mm <sup>2</sup>	Mean		17.9
	Category		II
Dimensional Stability N/mm <sup>2</sup>	NPD		
Bond Strength Fixed value N/mm <sup>2</sup>	NPD		
Active Soluble Salts	S2		
Reaction to Fire	NPD		Commission Decision 2000/605/EC
Water Absorption %	15		BS EN771-1
Water Vapour Permeability	NPD		
Direct Airborne Sound Insulation kg/m <sup>3</sup> (gross)	NPD		
Thermal Properties	NPD		
Durability Against Freeze Thaw	F2		
Dangerous Substances	NPD		

**The performance of the product(s) identified above is in conformity with the declared values**

Signed for and on behalf of the manufacturer by:

**Jason Hughes, Managing Director**

July 2020

Imperial Bricks Ltd  
Crowgreaves Farm  
Stableford  
Bridgnorth  
Shropshire  
WV15 5LT