


Plateswitches



Description

This uniquely shaped range of 10A light switches is easy to install, has clear white terminal markings and is supplied in individual protective bags suitable for display.

This range of plateswitches do not have to be de-rated for fluorescent loads and can be used by controlling lighting, door releases and bells.

Features

- Contemporary designed profile
- Convex rockers
- Only one size 4mm screwdriver needed
- Terminals have clear bold terminal markings
- Terminals have large lead-ins
- Range can be expanded using Gridswitch range
- 25-year guarantee

Range

1g 1w 10A	VC1202
1g 2w 10A	VC1203
2g 2w 10A	VC1204
3g 2w 10A	VC1205
4g 2w 10A	VC1244
6g 2w 10A	VC1245
Intermediate 10A	VC1246
3 pole fan isolator 10A	VC1247
Push to make/break 2w 'press'	VC1249
Push to make/break 2w – bell symbol	VC1249B

Technical Specification

Voltage rating	250Vac
Current Rating	10A
	X Rated
Contact gap	3mm
Frontplate material	Urea formaldehyde

Urea flammability classification UL94 grade V-0

No user serviceable parts

Standards

- BS 60669-1:2000

Back Boxes

Minimum recommended depth

	Flush	Dry lining	Surface
	25mm	35mm	25mm
1-3g	DB152	DB2540	V1220/E
4-6g	DB163	DB2541	V1223

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L	5	4	2	1