


# Aura eco 100

Cloakroom ventilation



## KEY FEATURES

- Axial fan
- Ventilation up to 70 m<sup>3</sup>/h
- Slim compact styling
- Quick and easy to fit
- Quiet - 26 dB(A)
- Low Watt motor - 5.6 W
- Low SFP - 0.33 W/l/s
- Compatible with 100 mm ducting
- IPX4 rating
- 2 year warranty



## Aura eco 100 range

Highly reliable, low energy fan in a modular design for ease of installation and maintenance. The Aura eco 100 is designed to provide quiet extraction for cloakroom applications. Recessed into a wall the Aura eco 100 provides slim, compact and discreet extraction for the property. With protection in mind, the Aura eco 100 comes with IPX4 ingress protection enabling installation anywhere within Zone 2.

Available with various control options; basic switching for on/off operation using an external switch; adjustable timer with fan activation via an external switch and an adjustable overrun between 2 and 30 minutes. Adjustable humidity timer enables activation of the fan via the use of an adjustable humidity sensor, 60 to 90% RH, or via a remote switch with an adjustable timer overrun of 2 to 30 mins. motion sensor time activates the fan with the use of an integral motion sensor with a timer overrun.



## MODELS


<b>Basic</b>	Control by Remote Switch
<b>Timer</b>	Adjustable timer overrun between 2 and 30 minutes
<b>Humidity Timer</b>	Adjustable Humidity 60 to 90% RH with adjustable timer
<b>Motion Sensor Timer</b>	Motion sensor activation



## TECHNICAL DATA


Specification	Aura eco 100B	Aura eco 100T	Aura eco 100HT	Aura eco 100MST
<b>Air flow m<sup>3</sup>/h / l/s</b>	70 / 17	70 / 17	70 / 17	70 / 17
<b>Fan type</b>	Axial	Axial	Axial	Axial
<b>Controls</b>	Basic	Timer	Humidity Timer	Motion Sensor Timer
<b>Mounting</b>	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling
<b>Sound pressure dB(A)@3 m</b>	26	26	26	26
<b>Power Watts</b>	5.6	5.6	5.6	5.6
<b>Amps</b>	0.035	0.035	0.035	0.035
<b>Specific Fan Power (SFP)</b>	0.33	0.33	0.33	0.33
<b>Duct diameter (mm)</b>	100	100	100	100
<b>Voltage</b>	230 V / 1 ph / 50-60 Hz	230 V / 1 ph / 50-60 Hz	230 V / 1 ph / 50-60 Hz	230 V / 1 ph / 50-60 Hz
<b>Rating</b>	IPX4	IPX4	IPX4	IPX4
<b>Material finish</b>	Plastic	Plastic	Plastic	Plastic
<b>Weight (kg)</b>	0.56	0.56	0.56	0.56
<b>Dimensions (H x W x D) mm</b>	150 x 150 x 102	150 x 150 x 102	150 x 150 x 102	150 x 150 x 102
<b>Part No.</b>	<b>9041347</b>	<b>9041348</b>	<b>9041349</b>	<b>9041350</b>

## DIMENSIONS (mm)



Model	A	B	C	D	E
<b>Aura eco 100</b>	150	102	100	122	17

## PERFORMANCE



## CONTROLS AND ACCESSORIES

A range of accessories including flexible and rigid ducting kits, controls, switches and grilles are available.

See accessories section for more details.

**Call: 01494 525252**

**Visit: [airflow.com](http://airflow.com)**



**Airflow Developments Limited**  
Aidelle House, Lancaster Road,  
Cressex Business Park,  
High Wycombe, Buckinghamshire,  
United Kingdom, HP12 3QP

E-mail: [info@airflow.com](mailto:info@airflow.com)  
Telephone: +44 (0) 1494 525252

[airflow.com](http://airflow.com)

© Airflow Developments Limited. Airflow Developments Limited reserve the right, in the interests of continuous development, to alter specifications without prior notice. All orders are accepted subject to our conditions of sale which are available on request



80001408 - Issue 1 09/23