

# ULTRAFLEX MATTING

## REINFORCEMENT FOR ULTRAFLEX MEMBRANE

UltraFlex Matting is a fiber glass matting specially developed to be used as a structural reinforcement for the polyurethane liquid membrane UltraFlex, ensuring minimum thickness for producing a long term waterproofing membrane. Resins used in the fiber interlacement are activated in contact with UltraFlex PU producing a 100% reinforced and adhered system.

### USES

- To be used with UltraFlex polyurethane membrane in waterproofing works.
- Ideal for refurbishing or for new construction works. Suitable for all surfaces.
- To ensure minimum recommended thickness while applying UltraFlex on wet-on-wet system.

### BENEFITS

Permits the UltraFlex application on wet-on-wet system, avoiding any waiting times between necessary coats, thus decreasing the application operational time on site.

It ensures the correct application of the membrane by guaranteeing the thickness of the membrane.

The multidirectional interlacing of the fibers provides better resistance to tensions in all directions while it increases the tensile strength of the system.

It contributes to the compensation of possible deficiencies in the support preparation.

Facilitates de crack bridging and minimizes surface levelling differences reinforcing the system against eventual breakages.

### STOCKING INSTRUCTIONS

Store in a dry place.

### DESCRIPTION

Thickness:	225 gr/sqm
Colour:	White
Packaging:	Rolls of 1m x 60 m / 13,5 Kg Rolls of 1m x 20 m / 4,5 Kg (boxes of 4 units)

### HANDLING

No special handling instructions have to be observed. Using gloves may be useful to protect hands against the fiber glass.

Consult the material and safety data sheet of the product (MSDS), or contact our technical department for further information.