

## PRODUCT INFORMATION

ISSUE 1 – MARCH 2020

Product code: UG255 | UG256 | UG257 | UG258  
SDC1 | SDC2 | SDC3 | SDC4

Polypipe In-floor Waste Adaptors are a quick and convenient method of adapting waste and overflow pipes to PVCu, Cast Iron and Clay drainage or soil pipes. The finned external gasket gives a water, air and odour tight seal to the internal bore of the drainage pipe.

The offset seals connect to all types of nominal sized waste pipe



### Key Benefits

- Choice of three Adaptors and a Drain Stopper for 4"/100mm/110mm pipe
- Ideal for floor level connections to PVCu, clay or cast iron nominal 4"/100mm/110mm drainage or soil pipe
- Seal is to the inside of the pipe, so they can be used even if cut pipe-end is at finished floor level
- Offset adaptor from 21.5mm push fit and solvent weld overflow
- Offset Adaptors from 32/40mm (1¼"/1½") waste pipe to BS EN 1451-1:2000 and BS EN 1329-1:2000
- Offset Adaptors from 50mm (2") waste pipe to BS EN 1451-1:2000 and BS EN 1329-1:2000
- Drain stopper provides a convenient temporary or permanent air and watertight stopper to 4"/100mm/110mm pipes.

### Installation Instructions

- Lubricate the finned gasket with Polypipe Joint Lubricant or Silicone Lubricant
- Fully insert into cut drainage or soil pipe end
- Lubricate the waste pipe and insert into the waste adaptor seal, ensuring that the pipe is inserted at least 25mm through the seal

#### UG255 SDC1



Adaptor from nominal 4"/100mm/110mm pipe to 21.5mm push fit or solvent weld overflow pipe

#### UG256 SDC2



Adaptor from nominal 4"/100mm/110mm pipe to 32/40mm (1¼"/1½") push fit or solvent weld pipe

#### UG257 SDC3



Adaptor from nominal 4"/100mm/110mm pipe to 50mm (2") push fit or solvent weld pipe

#### UG258 SDC4



Drain Stopper for nominal 4"/100mm/110mm pipe