rimco

Bolts



Brenton Padbolt

Brenton padbolts are used for securing flush mounted gates and shed doors in domestic and light commercial applications. They are pad-lockable and fixed with carriage bolts for added security.

Technical Data						
Bolt Length (mm)	102	100	150	200		
BoltØ(mm)	12	12	12	12		
Bolt Throw (mm)	12	30	45	45		
Plate Size (mm)	120 x 45	130 x 45	180 x 45	225 x 45		
Staple Keep Size L x W (mm)	83 x 23	56 x 33	56 x 33	56 x 33		
Max. Padlock Shackle Ø (mm)	10	10	10	10		
No. of Carriage Bolt Holes	4	4	4	4		
Carriage Bolt Ø (mm)	M6	M6	M6	M6		
No. of Screw Holes	6	6	6	6		
Screw Ø (mm)	4.0	4.0	4.0	4.0		

	Product Co	de	Bolt	Bolt	Pack	Carton
Epoxy Black	Zinc	Hot Dipped Galvanised	Length (mm)	Length (inch)	Qty (pcs)	Qty (packs)
		BAG - EXCI	UDES FIXIN	IGS		
BP4BB	BP4ZB	BP4GB	100	4	1	80
BP6BB	BP6ZB	BP6GB	150	6	1	60
BP8BB	BP8ZB	BP8GB	200	8	1	40 BTB01
		TIMBAG - FIX	INGS INCLU	JDED		
BP4BP	BP4ZP	BP4GP	100	4	1	10
BP6BP	BP6ZP	BP6GP	150	6	1	10
BP8BP	BP8ZP	BP8GP	200	8	1	10
						BTP01

BRENTON PADBOLT - ELONGATED KEEP						
BAG - EXCLUDES FIXINGS						
-	282004	-	102	4	1	5
						BTB01

Oval Padbolt

Oval padbolts are ideal for securing flush fitting narrow stile gates and doors in domestic and light commercial applications. They are pad-lockable and fixed with carriage bolts for added security.

					Technical	Data	
	and a			Bolt Length (mm)			100
				Bolt Ø (mm)			12
				Bolt Throw (mm)			40
				Plate Size L x W (mm)			55 x 100
				Staple Keep Size L x W (mm)		m)	73 x 24
				Max. Pac	llock Shackle Ø (r	nm)	10
				No. of Ca	arriage Bolt Holes		4
				Carriage	Bolt Ø (mm)		M6
	Product Code	9	E	Bolt	Bolt	Pack	Carton
Epoxy Black	Zinc	Hot Dipped Galvanised		ngth nm)	Length (inch)	Qty (pcs)	Qty (packs)

Diacit		Gaivaniscu	· · /	()	u ,	u		
BAG - EXCLUDES FIXINGS								
OP4BB	OP4ZB	OP4GB	100	4	1	60 BTB03		
TIMBAG - FIXINGS INCLUDED								
OP4BP	OP4ZP	OP4GP	100	4	1	10		
						BTP03		

Heavy Brenton Padbolt



Heavy brenton padbolts are used for securing flush mounted gates and shed doors in heavy domestic, commercial and agricultural applications. They are pad-lockable and fixed with carriage bolts for added security.

Technical Data						
Bolt Length (mm)		150	200	250	300	
Bolt Ø (mm)		16	16	16	16	
Bolt Throw (mm)		50	50	50	50	
Plate Size (mm)		170 x 60	220 x 60	270 x 60	320 x 60	
Staple Keep Size L x V		60 x 40	60 x 40	60 x 40	60 x 40	
Max. Padlock Shackle		14	14	14	14	
No. of Carriage Bolt H		4	4	4	4	
Carriage Bolt Ø (mm)		M6	M6	M6	M6	
No. of Screw Holes		6	6	6	6	
Screw Ø (mm)		4.0	4.0	4.0	4.0	
Hot Dipped Galvanised	Length (mm)		Length (inch)	Qt (pc		
	BAG -	EXCLUDES	FIXINGS			
282656	150		6	1	40	
282219	200		8	1	35	
282953	250		10	1	25	
282632	300		12	1	20	
					BTB01	
	TIMBAG	- FIXINGS I	NCLUDED			
287258	150		6	1	10	
287456	200		8	1	10	
287658	250		10	1	10	
287477	300		12	1	10	
					BTP01	

Slide Action Padbolt



Slide action padbolts are ideal for securing flush fitting gates and doors in domestic and light commercial applications when the bolt is exposed externally. They are padlockable and fixed with eight carriage bolts to prevent the bolt being wrenched from the door.

Technical Data					
Bolt Length (mm)	185				
Bolt Ø (mm)	9				
Bolt Throw (mm)	60				
Plate Size L x W (mm)	105 x 72				
Staple Keep Size L x W (mm)	76 x 25				
Max. Padlock Shackle Ø (mm)	8				
No. of Carriage Bolt Holes	8				
Carriage Bolt Ø (mm)	M6				

Produ Epoxy Black	ct Code Zinc	Bolt Length (mm)	Bolt Length (inch)	Pack Qty (pcs)	Carton Qty (packs)
DIACK		BAG - EXCLUDES	()	(P==)	(peerro)
282456	282789	185	7 5/16	1	80 BTB04
TIMBAG - FIXINGS INCLUDED					
287114	287585	185	7 5/16	1	10 BTP04