

bond it

Never compromise on quality!



COVER-IT HARDFLOOR PROTECTOR

Self-Adhesive Protection Sheet for Glass, Resilient and Hard Floor Surfaces



DECORATORS RANGE

Description:

A high performance, self-adhesive protection material for covering and protecting hard floors and surfaces against mess, dirt, spillages and staining, etc. whilst painting and decorating, plastering, tiling and general building and maintenance projects. Also suitable for use on glass and windows.

Uses

- Low tack, temporary, self-adhesive, waterproof hard surface protective film.
- For use on lacquered and plastic surfaces, aluminium, stainless steel, vinyl, hardwoods & laminates, glass, hard PVC surfaces, worktops, cabinets, cills and furniture surfaces.
- Easy application, simply unwind, roll and **COVER-IT**.
- Waterproof
- Safer to use than loose dust sheets and coverings heavy duty - tear resistant
- Can be applied and used between temperatures of +15°C to +25°C.

Application

Perform a compatibility test on an inconspicuous area prior to full application. Ensure the surface is free from dust, moisture and grease prior to application.

Flooring - Place the roll onto the floor with the open end facing away from the direction it is to be applied. Unpeel approx 300mm (12") of the protective cover and adhere it firmly to the surface. Simply push the roll forward slowly using either your foot or a soft brush, making sure it follows a straight line, smoothing it out as it unwinds to eliminate air bubbles or creases. Ensure film is safely and securely positioned before commencing work.

Other Surfaces - Unpeel approx 300mm (12") of **COVER-IT** and adhere it to the surface firmly by hand, simply unwind the roll smoothing down as you push the roll forward covering the surface.

Glass/ Windows - this product is also suitable for use on windows when painting window frames and sills.

Limitations

- In rare circumstances **COVER-IT** can leave sticky residues on certain surfaces so it is recommended test areas be carried out prior to application.
- Always check that **COVER-IT** is securely adhered to the surface before commencing any work to reduce slips, trips and falls.
- Replace **COVER-IT** after 4 weeks. Any unexpected residue can be easily removed by hand or with Bond It

MULTI-WIPES - dependant on surface, check the compatibility of any surfaces with the wipes in an inconspicuous area first. Bond It **FOIL SAFE CLEANER** may also be used if the surface is suitable.

- Do not use underfloor heating whilst **COVER-IT** is in position or 24 hours prior to application.
- In heavily trafficked areas or if exposed to excessive light or heat, replace at least once a week, checking for any residues left on the surface
- Disposable - single use only.
- Slippery when wet.



Removal

Easy and simple - the low tack adhesive will allow for easy removal. Lift each edge in turn and pull back towards the middle to keep any contaminants central on the roll ensuring any spills are covered and cannot escape before lifting the whole sheet.

Shelf Life

12 months from date of manufacture.

Storage Conditions

Store in cool dry conditions between 5 and 25°C. Safe in normal use however as a precaution keep polythene outer packaging away from children.

Disposal of Containers

Dispose of in accordance with local regulations – sheet is polythene. Container is cardboard - widely recycled locally.

Health & Safety

Please refer to separate material safety data sheet for full handling, use and storage instructions. Keep out of reach of children. It is the users responsibility to determine suitability for use. If in doubt contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control. It is recommended that users make their own tests to determine suitability.

Specification Summary

| | |
|-----------|----------------------------|
| Adhesive | Pressure sensitive acrylic |
| Thickness | < 28 microns |
| Film | Polyolefin |

Product Details:

| | | |
|-----------------|---------------|---------------|
| Code: | BDCIHP25 | BDCIHP50 |
| Size: | 600mm x 25M | 600mm x 50M |
| Colour: | Blue | Blue |
| Barcode: | 5060021369703 | 5060021369833 |

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position.

Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Part of the Bond It Decorating Sundries Range



Certificate Number:
6152
ISO 9001; ISO 14001;
ISO 45001



BOND IT
 Head Office: Unit G16 River Bank Way, Lowfields Business Park,
 Elland, West Yorkshire HX5 9DN.
 Telephone: +44 (0)1422 315300 Fax +44 (0)1422 315310
 Email: salesuk@bonditgroup.com Website: www.bonditgroup.com



V4 23/10/17
 Supercedes: V3 20/03/17