

Soudal Express Roof & Gutter Sealant

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Product name : Soudal Express Roof & Gutter Sealant
 Registration number REACH : Not applicable (mixture)
 Product type REACH : Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Relevant identified uses

Sealant

1.2.2 Uses advised against

No uses advised against known

1.3 Details of the supplier of the safety data sheet:

Supplier of the safety data sheet

SODAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 ☐ +32 14 42 65 14
 msds@soudal.com

Manufacturer of the product

SODAL N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 ☐ +32 14 42 65 14
 msds@soudal.com

1.4 Emergency telephone number:

24h/24h (Telephone advice: English, French, German, Dutch):
 +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

2.1.1 Classification according to Regulation EC No 1272/2008

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Flam. Liq.	category 3	H226: Flammable liquid and vapour.
STOT SE	category 3	H336: May cause drowsiness or dizziness.

2.1.2 Classification according to Directive 67/548/EEC-1999/45/EC

Classified as dangerous in accordance with the criteria of Directives 67/548/EEC and 1999/45/EC

R10 - Flammable.

R66 - Repeated exposure may cause skin dryness or cracking.

R67 - Vapours may cause drowsiness and dizziness.

2.2 Label elements:

Labelling according to Regulation EC No 1272/2008 (CLP)



Signal word

Warning

H-statements

H226

Flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

P-statements

P101

If medical advice is needed, have product container or label at hand.

Soudal Express Roof & Gutter Sealant

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves and eye protection/face protection.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370 + P378	In case of fire: Use suitable extinguishing medium to extinguish.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling according to Directive 67/548/EEC-1999/45/EC (DSD/DPD)

R-phrases

10	Flammable
66	Repeated exposure may cause skin dryness or cracking
67	Vapours may cause drowsiness and dizziness

S-phrases

(02)	(Keep out of the reach of children)
(46)	(If swallowed, seek medical advice immediately and show this container or label)

2.3 Other hazards:

CLP

May be ignited by sparks
Slightly irritant to eyes

DSD/DPD

May be ignited by sparks
Slightly irritant to eyes

SECTION 3: Composition/information on ingredients

3.1 Substances:

Not applicable

3.2 Mixtures:

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to DSD/DPD	Classification according to CLP	Note	Remark
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119471843-32		C=20%	Xn; R65 R10 R52-53 R66 R67	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 3; H412	(1)(10)	UVCB
(benzene, conc<0.1%)						

(1) For R-phrases and H-statements in full: see heading 16

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1 Description of first aid measures:

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Narcosis. Feeling of weakness. Dizziness. Headache. Nausea. Disturbances of consciousness.

After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Revision number: 0300

Product number: 32461

2 / 11

Soudal Express Roof & Gutter Sealant

After eye contact:

Slight irritation. ON CONTINUOUS EXPOSURE/CONTACT: Irritation of the eye tissue.

After ingestion:

Nausea. Irritation of the gastric/intestinal mucosa.

4.2.2 Delayed symptoms

No effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

5.1.1 Suitable extinguishing media:

Water spray. Polyvalent foam. Dry chemical powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

Solid water jet ineffective as extinguishing medium.

5.2 Special hazards arising from the substance or mixture:

Upon combustion: CO and CO₂ are formed.

5.3 Advice for firefighters:

5.3.1 Instructions:

No specific fire-fighting instructions required.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2 Environmental precautions:

Contain leaking substance. Dam up the liquid spill. Prevent spreading in sewers. Use appropriate containment to avoid environmental contamination.

6.3 Methods and material for containment and cleaning up:

Take up liquid spill into a non combustible material e.g.: sand/earth. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers.

Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4 Reference to other sections:

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1 Precautions for safe handling:

Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system.

Insufficient ventilation: keep naked flames/sparks away. Observe normal hygiene standards. Keep container tightly closed. Remove contaminated clothing immediately. Do not discharge the waste into the drain.

7.2 Conditions for safe storage, including any incompatibilities:

7.2.1 Safe storage requirements:

Ventilation at floor level. Meet the legal requirements. Store at room temperature. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Plastics.

7.2.4 Non suitable packaging material:

No data available

7.3 Specific end use(s):

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

Soudal Express Roof & Gutter Sealant

SECTION 8: Exposure controls/personal protection

8.1 Control parameters:

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL - Workers

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1500 mg/m ³	
	Long-term systemic effects dermal	300 mg/kg bw/day	

DNEL - General population

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	900 mg/m ³	
	Long-term systemic effects dermal	300 mg/kg bw/day	
	Long-term systemic effects oral	300 mg/kg bw/day	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2 Exposure controls:

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system.

Insufficient ventilation: keep naked flames/sparks away. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection:

High gas/vapour concentration: gas mask with filter type A.

b) Hand protection:

Gloves.

- materials (good resistance)

Neoprene, natural rubber.

c) Eye protection:

Face shield.

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical form	Viscous
Odour	Naphtha odour
Odour threshold	No data available
Colour	Black
Particle size	Not applicable
Explosion limits	0.6 - 7.0 vol %
Flammability	Flammable
Log Kow	Not applicable (mixture)
Dynamic viscosity	>7 mm ² /s ; 40 °C
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	130-170 °C
Flash point	> 31°C
Evaporation rate	No data available
Relative vapour density	No data available

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Revision number: 0300

Product number: 32461

4 / 11

Soudal Express Roof & Gutter Sealant

Vapour pressure	No data available
Solubility	water ; insoluble organic solvents ; soluble
Relative density	1.0
Decomposition temperature	No data available
Auto-ignition temperature	> 200°C
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2 Other information:

Extrapolated kinematic viscosity	No data available
Absolute density	1005 kg/m ³

SECTION 10: Stability and reactivity

10.1 Reactivity:

May be ignited by sparks.

10.2 Chemical stability:

Stable under normal conditions.

10.3 Possibility of hazardous reactions:

No data available.

10.4 Conditions to avoid:

Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system.
Insufficient ventilation: keep naked flames/sparks away.

10.5 Incompatible materials:

No data available.

10.6 Hazardous decomposition products:

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

11.1.1 Test results

Acute toxicity

Soudal Express Roof & Gutter Sealant

No (test) data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000mg/kg bw		Rat (male/female)	Read-across	
Oral	LD50	OECD 401	> 15000mg/kg bw		Rat (male/female)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3160mg/kg bw	24 h	Rabbit (male/female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 5000mg/m ³ air	8 h	Rat (male)	Read-across	

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

Soudal Express Roof & Gutter Sealant

No (test) data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		1; 24; 48; 72; 168 hours	Rabbit	Read-across	
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

Judgement is based on the relevant ingredients

Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Soudal Express Roof & Gutter Sealant

Respiratory or skin sensitisation

Soudal Express Roof & Gutter Sealant

No (test) data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (male/female)	Read-across	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

Soudal Express Roof & Gutter Sealant

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Dermal					Skin dryness or cracking			Literature study
Inhalation (vapours)					Drowsiness, dizziness			Literature study

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	OECD 422	> 1000mg/kg bw/day		No effect		Rat (male/female)	Read-across
Oral	NOAEL	Equivalent to OECD 408	> 5000mg/kg bw/day		No effect	13 weeks (daily)	Rat (male/female)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 2200mg/m ³ air		No effect	14 weeks (6h/day, 5 days/week)	Rat (female)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 10400mg/m ³ air		No effect	13 weeks (6h/day, 5 days/week)	Rat (male/female)	Read-across

Classification is based on the relevant ingredients

Conclusion

May cause drowsiness or dizziness.

Low sub-chronic toxicity by the oral route

Mutagenicity (in vitro)

Soudal Express Roof & Gutter Sealant

No (test) data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Test substrate	Effect	Value determination
Negative	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Read-across
Negative	OECD 471	Bacteria (S.typhimurium)		Read-across

Mutagenicity (in vivo)

Soudal Express Roof & Gutter Sealant

No (test) data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 474		Mouse (male/female)		Read-across
Negative	Equivalent to OECD 478	5 days (6h/day)	Rat (male/female)		Read-across

Carcinogenicity

Soudal Express Roof & Gutter Sealant

No (test) data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Organ	Effect
Inhalation (vapours)	NOAEC	Equivalent to OECD 453	> 2200mg/m ³ air	105 weeks (6h/day, 5 days/week)	Rat (female)	Read-across		No effect

Reproductive toxicity

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Revision number: 0300

Product number: 32461

6 / 11

Soudal Express Roof & Gutter Sealant

Soudal Express Roof & Gutter Sealant

No (test)data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Effects on fertility	NOAEL	Equivalent to OECD 421	> 1000mg/kg bw/day		Rat (male/female)	No effect		Read-across

Judgement is based on the relevant ingredients

Conclusion CMR

Not classified for reprotoxic or developmental toxicity

Not classified for mutagenic or genotoxic toxicity

Not classified for carcinogenicity

Toxicity other effects

Soudal Express Roof & Gutter Sealant

No (test)data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
				Skin dryness or cracking			Literature study

Classification is based on the relevant ingredients

Conclusion

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity:

Soudal Express Roof & Gutter Sealant

No (test)data on the mixture available

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	>10 - <30 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EL50	OECD 202	>22 - <46 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
	NOEL	OECD 201	< 1 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEL		0.182 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic invertebrates	NOELR		0.317 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Nominal concentration

Judgement is based on the relevant ingredients of the mixture

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2 Persistence and degradability:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	89 %	28 day(s)	Experimental value

Conclusion

Contains readily biodegradable component(s)

12.3 Bioaccumulative potential:

Soudal Express Roof & Gutter Sealant

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Revision number: 0300

Product number: 32461

7 / 11

Soudal Express Roof & Gutter Sealant

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

No test data of component(s) available

12.4 Mobility in soil:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	89.8 %	0 %	6.2 %	1.8 %	2.2 %	Calculated value

Conclusion

No straightforward conclusion can be drawn based upon the available numerical values

12.5 Results of PBT and vPvB assessment:

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6 Other adverse effects:

Soudal Express Roof & Gutter Sealant

Global warming potential (GWP)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

Ground water

Ground water pollutant

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Global warming potential (GWP)

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1 Waste treatment methods:

13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other dangerous substances). Depending on branch of industry and production process, also other waste codes may be applicable. Hazardous waste according to Directive 2008/98/EC.

13.1.2 Disposal methods

Incinerate under surveillance with energy recovery. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1 UN number:

Transport	Not subject
-----------	-------------

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

Hazard identification number	
Class	
Classification code	

14.4 Packing group:

Packing group	
Labels	

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Revision number: 0300

Product number: 32461

8 / 11

Soudal Express Roof & Gutter Sealant

Special provisions	
Limited quantities	
Specific mention	Viscous liquid with flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$, which meets the conditions indicated in 2.2.3.1.5 of ADR, is not subject

Rail (RID)

14.1 UN number:

Transport	Not subject
-----------	-------------

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

Hazard identification number	
Class	
Classification code	

14.4 Packing group:

Packing group	
Labels	

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	
Limited quantities	
Specific mention	Viscous liquid with flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$, which meets the conditions indicated in 2.2.3.1.5 of RID, is not subject

Inland waterways (ADN)

14.1 UN number:

Transport	Not subject
-----------	-------------

14.2 UN proper shipping name:

14.3 Transport hazard class(es):

Class	
Classification code	

14.4 Packing group:

Packing group	
Labels	

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	
Limited quantities	
Specific mention	Viscous liquid with flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$, which meets the conditions indicated in 2.2.3.1.5 of ADN, is not subject

Sea (IMDG/IMSBC)

14.1 UN number:

UN number	3295
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Hydrocarbons, liquid, n.o.s.
----------------------	------------------------------

14.3 Transport hazard class(es):

Class	3
-------	---

14.4 Packing group:

Packing group	III
Labels	3

14.5 Environmental hazards:

Marine pollutant	-
Environmentally hazardous substance mark	no

14.6 Special precautions for user:

Special provisions	223
Limited quantities	Combination packagings: not more than 5 liters per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
Specific mention	Viscous liquid with flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$, which meets the conditions indicated in 2.3.2.5 of IMDG, is not subject to IMDG Code chapters 4.1, 5.2 and 6.1

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

Annex II of MARPOL 73/78	Not applicable, based on available data
--------------------------	---

Air (ICAO-TI/IATA-DGR)

14.1 UN number:

UN number	3295
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Hydrocarbons, liquid, n.o.s.
----------------------	------------------------------

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Revision number: 0300

Product number: 32461

9 / 11

Soudal Express Roof & Gutter Sealant

14.3 Transport hazard class(es):

Class	3
-------	---

14.4 Packing group:

Packing group	III
Labels	3

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
--	----

14.6 Special precautions for user:

Special provisions	A3
Special provisions	A324
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
20 %	

European drinking water standards (Directive 98/83/EC)

(benzene, conc<0.1%)

Parameter	Parametric value	Note	Reference
Benzene	1 µg/l		Listed in Annex I, Part B, of Directive 98/83/EC on the quality of water intended for human consumption.

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects,2. Articles not complying with paragraph 1 shall not be placed on the market.3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304,4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN),5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'
hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — "whoopie" cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs,

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Revision number: 0300

Product number: 32461

10 / 11

Soudal Express Roof & Gutter Sealant

—stink bombs.2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
"For professional users only".3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

National legislation The Netherlands

Soudal Express Roof & Gutter Sealant

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 03
Waterbezwaarlijkheid	11

National legislation Germany

Soudal Express Roof & Gutter Sealant

WGK	2; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	---

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

TA-Luft	5.2.5
---------	-------

National legislation France

Soudal Express Roof & Gutter Sealant

No data available

National legislation Belgium

Soudal Express Roof & Gutter Sealant

No data available

Other relevant data

Soudal Express Roof & Gutter Sealant

No data available

15.2 Chemical safety assessment:

No chemical safety assessment has been conducted.

SECTION 16: Other information

Full text of any R-phrases referred to under headings 2 and 3:

- R10 Flammable
- R52 Harmful to aquatic organisms
- R53 May cause long-term adverse effects in the aquatic environment
- R65 Harmful: may cause lung damage if swallowed
- R66 Repeated exposure may cause skin dryness or cracking
- R67 Vapours may cause drowsiness and dizziness

Full text of any H-statements referred to under headings 2 and 3:

- H226 Flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H336 May cause drowsiness or dizziness.
 - H412 Harmful to aquatic life with long lasting effects.
- (*) = INTERNAL CLASSIFICATION BY BIG
PBT-substances = persistent, bioaccumulative and toxic substances
DSD Dangerous Substance Directive
DPD Dangerous Preparation Directive
CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: ATP4

Publication date: 2002-11-04

Date of revision: 2014-12-05

Revision number: 0300

Product number: 32461

11 / 11