



## Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Reference nr: 231631

Unique identification code of the product-type

**Trade Construction Silicone**

Intended use or uses of the construction product

**Sealants for facade for interior and exterior application**

**Sealants used for glazing applications**

**Sealants used for sanitary applications**

Name and contact address of the manufacturer as required pursuant to Article 11(5)

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

**System 3: for reaction to fire**

**System 3: for essential characteristics**

Construction product in accordance with applicable harmonised specifications

**EN 15651-1:2012: Type F-EXT-INT 12.5E**

**EN 15651-2:2012: Type G**

**EN 15651-3:2012: Type S1**

The notified body

**The notified body GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.**

**Declared Performance: EN 15651-1:2012**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties at break after water immersion	≥ 25%	
Durability	Pass	

**Conditioning:** Method A

**Test Substrate:** aluminium, mortar

**Declared Performance: EN 15651-2:2012**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-2:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elastic recovery	≥ 60%	
Adhesion/cohesion after exposure to heat, water and artificial light	NF	
Durability	Pass	

**Conditioning:** Method A

**Test Substrate:** aluminium, glass

**Declared Performance: EN 15651-3:2012**

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties at break after water immersion	≥ 25%	
Microbiological growth	0	
Durability	Pass	

**Conditioning:** Method A

**Test Substrate:** aluminium, glass



The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx  
Senior Technical Product Manager  
Soudal NV- Belgium

## CE marking

In accordance with the CPR Regulation (EU) N° 305/2011



NB 0074

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium  
20

Reference nr: 231631

EN 15651-1:2012

EN 15651-2:2012

EN 15651-3:2012

Sealants for facade for interior and exterior application

Sealants used for glazing applications

Sealants used for sanitary applications

### Trade Construction Silicone

EN 15651-1:2012: Type F-EXT-INT 12.5E

EN 15651-2:2012: Type G

EN 15651-3:2012: Type S1

**Conditioning:** Method A

**Test Substrate:** aluminium, mortar, glass

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties at break after water immersion	≥ 25%	
Elastic recovery	≥ 60%	
Adhesion/cohesion after exposure to heat, water and artificial light	NF	
Microbiological growth	0	
Durability	Pass	



## UKCA Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

UK Reference nr DOP: 231631UK

Unique identification code of the product-type

**Trade Construction Silicone**

Intended use or uses of the construction product

**Sealants for facade for interior and exterior application**

**Sealants used for glazing applications**

**Sealants used for sanitary applications**

Name and contact address of the manufacturer as required pursuant to Article 11(5)

**Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium**

Authorised representative

**Soudal (UK) Ltd, Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth**

**B77 5PN Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth B77 5PN.**

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

**System 3: for reaction to fire**

**System 3: for essential characteristics**

Construction product in accordance with applicable designated standards

**BS EN 15651-1:2012: Type F-EXT-INT 12.5E**

**BS EN 15651-2:2012: Type G**

**BS EN 15651-3:2012: Type S1**

Approved Body

**4ward Testing, AB 2538, has carried out Determination of the Product Type under system 3.**



**Declared Performance: BS EN 15651-1:2012**

Essential Characteristics	Performance	Designated Technical Specification
Reaction to fire	E	BS EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NPD	
Tensile properties at break after water immersion	NPD	
Durability	Pass	

**Conditioning:** Method A

**Test substrate:** aluminium, mortar

**Declared Performance: BS EN 15651-2:2012**

Essential Characteristics	Performance	Designated Technical Specification
Resistance to flow	≤ 3 mm	BS EN 15651-2:2012
Loss of volume	NPD	
Water and air tightness		
Elastic recovery	NPD	
Adhesion/cohesion after exposure to heat, water and artificial light	NPD	
Durability	Pass	

**Conditioning:** Method A

**Test substrate:** aluminium, glass

**Declared Performance: BS EN 15651-3:2012**

Essential Characteristics	Performance	Designated Technical Specification
Resistance to flow	≤ 3 mm	BS EN 15651-3:2012
Loss of volume	NPD	
Water and air tightness		
Tensile properties at maintained extension after water immersion	NPD	
Tensile properties at break after water immersion	NPD	
Microbiological growth	NPD	
Durability	Pass	

**Conditioning:** Method A

**Test substrate:** aluminium, glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.


Signed for on behalf of the manufacturer by



Ing. W. Dierckx  
Senior Technical Product Manager  
Soudal NV- Belgium

**UKCA marking**

In accordance with the CPR Regulation (EU) N° 305/2011

 <b>AB 2538</b>		
<b>Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium</b> 21 UK Reference nr DOP: 231631UK		
BS EN 15651-1:2012 BS EN 15651-2:2012 BS EN 15651-3:2012		
Sealants for facade for interior and exterior application Sealants used for glazing applications Sealants used for sanitary applications		
<b>Trade Construction Silicone</b> BS EN 15651-1:2012: Type F-EXT-INT 12.5E BS EN 15651-2:2012: Type G BS EN 15651-3:2012: Type S1		
<b>Conditioning:</b> Method A <b>Test substrate:</b> aluminium, mortar, glass		
Essential Characteristics	Performance	Designated Technical Specification
Reaction to fire	E	BS EN 15651-1:2012 BS EN 15651-2:2012 BS EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NPD	
Tensile properties at break after water immersion	NPD	
Elastic recovery	NPD	
Adhesion/cohesion after exposure to heat, water and artificial light	NPD	
Microbiological growth	NPD	
Durability	Pass	