

Technical Data

13 Amp RCD Switched Socket Outlet

Brief product description:

The subtle design will blend with any décor - suitable for domestic or commercial installations.

Features:

- White moulded round edge, sleek and slim with softly rounded edges
- Power socket for standard 3 pin UK plug
- Integrated RCD to prevent the leakage of electrical current
- Easy to install, supplied with fixing screws and installation instructions
- Angled in-line colour coded terminals with backed out screws for fast installation
- Screw cover caps for a sleek appearance
- Twin earth fitted as standard for high integrity circuits
- Anti-microbial certified manufactured using high grade thermoset Urea which effectively inhibits the growth of infectious diseases, including MRSA, E-Coli, Salmonella and Klebsiella Pneumonia bacteria

Product Images






822RCD

Technical Specifications		
Standard(s)	BS EN 60669-2-1, BS 7288: 1990	UK
Rating	13 Amp	CA
Maximum Load	3120 Watts, 240V AC	(f
RCD Rating	30mA, Trip speed 40 ms	
RCD Type	Latching Type	
Terminal Capacity	4 x 1.0mm², 4 x 1.5mm², 2 x 2.5mm² & 1 x 4.0mm²	
RoHS Directive	Yes	
WEEE Directive	Yes	
Mounting Box Depth (Min)	35mm, 10mm spacer provided for shallower boxes	
Fixing Centres	120.6mm	



13 Amp RCD Switched Socket Outlet

Line Diagrams



Packaging Information

822RCD

Cat No.	Description	Packaging Type			Pack Quantity			Barcode		
		Product	Inner Box	Outer Box	Each	Inner Box	Outer Box	Individual	Inner Box	Outer Box
822RCD	13A 2G RCD SW SKT	Printed Bag	Printed Carton	Printed Carton	1	5	50	5050765008242	5050765008259	5050765008266

Weights & Dimensions Cat No. Description Dimensions (H x W x D) cm Weight (kg) CBM (m³) Unpacked Product Unpacked Product Packed Inner Box Outer Box Packed Outer Outer Box Inner Product Product Box Box

0.286

0.291

1.54

15.78

13A 2G RCD SW SKT 8.6 x 14.6 x 3.9 14.8 x 9.1 x 4.3 9.7 x 16.7 x 20.2 22.1 x 35.1 x 49.3

0.03824