

110V TRIPOD WORK LIGHT



Product Features

- Robust aluminium tripod and LED heads
- Supplied with toughened glass for onsite applications
- Twin version option with 2x110V 16A outlet sockets
- Supplied with 3000mm 3 core rubber cable 110V 16A plug to EN 60309



CAT NO.	TYPE	LUMINAIRE LUMENS	WATTAGE
LSLSTW181V	Single Head	1800	22W
LSLTTW2181V	Twin Head	2 x 1800	2 x 22W
LSLTTWOS2181V	Twin Head with Outlets	2 x 1800	2 x 22W

CAT NO.	WEIGHT (kg)	CRI	FREQUENCY	IK RATING	CABLE TYPE	CABLE LENGTH	TEMP RANGE (°C)	AMBIENT TEMP RATED LIFE (°C)
LSLSTW181V	3.34	>80	50-60	IK08	H07RN-F 1.0mm ²	3000mm	-0 to +25	25
LSLTTW2181V	4.85	>80	50-60	IK08	H07RN-F 1.0mm ²	3000mm	-0 to +25	25
LSLTTWOS2181V	6.02	>80	50-60	IK08	H07RN-F 1.5mm ²	3000mm	-0 to +25	25



STANDARD	DESCRIPTION
60598-1	Luminaires – General requirements
60598-2-4	Luminaires – Portable
61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits – for harmonic current emissions
61000-3-3	Lamp controlgear – Part 1: General and safety requirements
61547	Equipment for general lighting purposes – EMC immunity requirements
55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

LUCECO

This luminaire contains built-in LED lamps.

A++
A+
A
C
D
E

} LED

The lamps cannot be changed in the luminaire.

874/2012

