

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Issue date: 2019/2/17 Version: 1.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : CEDRAL TOUCH-UP PAINT 60170
Product code : 6704410
Type of product : Paint
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use, Consumer use
Use of the substance/mixture : Touch-up paint for fiber cement siding.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ETERNIT France
14 AVENUE DE L'ILE DE FRANCE
27200 VERNON - FRANCE
T +33 (0) 2 32 64 31 31 - F +33 (0) 2 32 51 82 21
commercial.vernon@etexgroup.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazardous ingredients :

2-methylisothiazol-3(2H)-one

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H317 - May cause an allergic skin reaction.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P280 - Wear eye protection/face protection, protective clothing, protective gloves. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P501 - Dispose of contents/container to an approved waste disposal plant.
UFI	: 6GUX-Y9FJ-GM07-Q8TN

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not established.

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Titanium dioxide substance with national workplace exposure limit(s) (BE, DK, FR, GB, LT)	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	≥ 10 – < 20	Not classified
substance with national workplace exposure limit(s) (BE, GB)	(CAS-No.) 1317-65-3 (EC-No.) 215-279-6	≥ 5 – < 10	Not classified
1-methoxy-2-propanol; monopropylene glycol methyl ether substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (BE, DE, DK, FR, GB, LT, NL)	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3	≥ 1 – < 2,5	Flam. Liq. 3, H226 STOT SE 3, H336
KAOLIN substance with national workplace exposure limit(s) (BE, DK, GB)	(CAS-No.) 1332-58-7 (EC-No.) 310-194-1	≥ 0,1 – < 0,5	Not classified
3-Iod-2-propinylbutylcarbamate	(CAS-No.) 55406-53-6 (EC-No.) 259-627-5 (EC Index-No.) 616-212-00-7	≥ 0,1 – < 0,5	Acute Tox. 3 (Inhalation), H331 Acute Tox. 4 (Oral), H302 STOT RE 1, H372 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410
ammonia%	(CAS-No.) 1336-21-6 (EC-No.) 215-647-6 (EC Index-No.) 007-001-01-2	≥ 0,1 – < 0,5	Skin Corr. 1B, H314 Aquatic Acute 1, H400
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	< 0,1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
2-methylisothiazol-3(2H)-one	(CAS-No.) 2682-20-4 (EC-No.) 220-239-6 (EC Index-No.) 613-326-00-9	< 0,1	Acute Tox. 2 (Inhalation), H330 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
ammonia%	(CAS-No.) 1336-21-6 (EC-No.) 215-647-6 (EC Index-No.) 007-001-01-2	(5 ≤C < 100) STOT SE 3, H335
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	(0,05 ≤C < 100) Skin Sens. 1, H317
2-methylisothiazol-3(2H)-one	(CAS-No.) 2682-20-4 (EC-No.) 220-239-6 (EC Index-No.) 613-326-00-9	(0,0015 ≤C ≤ 100) Skin Sens. 1A, H317

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep only in original container. Protect from sunlight.
Storage temperature : 5 – 35 °C
Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
Belgium - Occupational Exposure Limits	
Local name	1-Méthoxy-2-propanol # 1-Methoxy-2-propanol
Limit value (mg/m ³)	184 mg/m ³
Limit value (ppm)	50 ppm
Short time value (mg/m ³)	369 mg/m ³
Short time value (ppm)	100 ppm
Remark (BE)	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 21/01/2020
Denmark - Occupational Exposure Limits	
Local name	1-Methoxy-2-propanol (Propylenglycolmonomethylether)
Grænsevædi (8 timer) (mg/m ³)	185 mg/m ³
Grænsevædi (8 timer) (ppm)	50 ppm
Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi)
Regulatory reference	BEK nr 1458 af 13/12/2019
France - Occupational Exposure Limits	
Local name	1-Méthoxy-2-propanol (Ether méthylique du propylène-glycol) (1-Méthoxypropane-2-ol)

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
VME (mg/m ³)	188 mg/m ³
VME (ppm)	50 ppm
VLE (mg/m ³)	375 mg/m ³
VLE (ppm)	100 ppm
Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)
Germany - Occupational Exposure Limits (TRGS 900)	
TRGS 900 Local name	1-Methoxy-2-propanol
Occupational exposure limit value (mg/m ³)	370 mg/m ³
Occupational exposure limit value (ppm)	100 ppm
Limitation of exposure peaks	2(l)
TRGS 900 Remark	DFG;EU;Y
TRGS 900 Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
TRGS 903 Local name	1-Methoxypropan-2-ol
TRGS 903 Biological limit value	15 mg/l Parameter: 1-Methoxypropan-2-ol - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2012 DFG
TRGS 903 Regulatory reference	TRGS 903
Lithuania - Occupational Exposure Limits	
Local name	1-metoksipropanolis-2 (propilenglikolio monometileris, PGME)
IPRV (mg/m ³)	190 mg/m ³
IPRV (ppm)	50 ppm
TPRV (mg/m ³)	300 mg/m ³
TPRV (ppm)	75 ppm
Remark (LT)	O (medžiaga į organizmą gali prasiskverbti pro nepažeistą odą)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Netherlands - Occupational Exposure Limits	
Local name	1-Methoxy-2-propanol
Grenswaarde TGG 8H (mg/m ³)	375 mg/m ³
Grenswaarde TGG 15MIN (mg/m ³)	563 mg/m ³
Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2020
United Kingdom - Occupational Exposure Limits	
Local name	1-Methoxypropan-2-ol
WEL TWA (mg/m ³)	375 mg/m ³
WEL TWA (ppm)	100 ppm
WEL STEL (mg/m ³)	560 mg/m ³
WEL STEL (ppm)	150 ppm

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

(1317-65-3)

Belgium - Occupational Exposure Limits

Local name	Calcium (carbonate de) # Calciumcarbonaat
Limit value (mg/m ³)	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 21/01/2020

United Kingdom - Occupational Exposure Limits

Local name	Calcium carbonate (Limestone, Marble)
WEL TWA (mg/m ³)	10 mg/m ³ total inhalable 4 mg/m ³ respirable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

3-Iod-2-propinylbutylcarbamate (55406-53-6)

Germany - Occupational Exposure Limits (TRGS 900)

TRGS 900 Local name	3-Iod-2-propinyl-butylcarbamate
Occupational exposure limit value (mg/m ³)	0,058 mg/m ³
Occupational exposure limit value (ppm)	0,005 ppm
Limitation of exposure peaks	2(l)
TRGS 900 Remark	DFG;Y;Sh;11
TRGS 900 Regulatory reference	TRGS900

KAOLIN (1332-58-7)

Belgium - Occupational Exposure Limits

Local name	Kaolin (fraction alvéolaire) # Kaolien (inadembare fractie)
Limit value (mg/m ³)	2 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 21/01/2020

Denmark - Occupational Exposure Limits

Local name	Kaolin
Grænsevædi (8 timer) (mg/m ³)	2 mg/m ³ respirabel
Regulatory reference	BEK nr 1458 af 13/12/2019

United Kingdom - Occupational Exposure Limits

Local name	Kaolin
WEL TWA (mg/m ³)	2 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Titanium dioxide (13463-67-7)

Belgium - Occupational Exposure Limits

Local name	Titane (dioxyde de) # Titaandioxide
Limit value (mg/m ³)	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 21/01/2020

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Titanium dioxide (13463-67-7)	
Denmark - Occupational Exposure Limits	
Local name	Titandioxid
Grænsevædi (8 timer) (mg/m ³)	6 mg/m ³ beregnet som Ti
Regulatory reference	BEK nr 1458 af 13/12/2019
France - Occupational Exposure Limits	
Local name	Titane (dioxyde de), en Ti
VME (mg/m ³)	10 mg/m ³
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Lithuania - Occupational Exposure Limits	
Local name	Titano dioksidas
IPRV (mg/m ³)	5 mg/m ³
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (mg/m ³)	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Protective clothing. Gloves.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Colour	: Blue.
Odour	: slight.
Odour threshold	: No data available
pH	: 9,2
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1,26
Density	: 1260 kg/m ³
Solubility	: Dilutable with water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 1984,127 mm ² /s
Viscosity, dynamic	: 2500 mPa·s (Brookfield, M4V20)
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 38 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal))
-----------------	---

(1317-65-3)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one (2634-33-5)

ATE CLP (oral)	500 mg/kg bodyweight
----------------	----------------------

3-Iod-2-propinylbutylcarbamate (55406-53-6)

ATE CLP (oral)	500 mg/kg bodyweight
----------------	----------------------

ATE CLP (gases)	700 ppmv/4h
-----------------	-------------

ATE CLP (vapours)	3 mg/l/4h
-------------------	-----------

ATE CLP (dust,mist)	0,5 mg/l/4h
---------------------	-------------

2-methylisothiazol-3(2H)-one (2682-20-4)

ATE CLP (oral)	100 mg/kg bodyweight
----------------	----------------------

ATE CLP (dermal)	300 mg/kg bodyweight
------------------	----------------------

ATE CLP (gases)	100 ppmv/4h
-----------------	-------------

ATE CLP (vapours)	0,5 mg/l/4h
-------------------	-------------

ATE CLP (dust,mist)	0,05 mg/l/4h
---------------------	--------------

Titanium dioxide (13463-67-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
---------------	--

LD50 dermal rabbit	> 5000 mg/kg
--------------------	--------------

LC50 inhalation rat (mg/l)	> 6,8 mg/l/4h
----------------------------	---------------

Skin corrosion/irritation	: Not classified pH: 9,2
Serious eye damage/irritation	: Not classified pH: 9,2
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
----------------------------	--

NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)
----------------------------	---

NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
-------------------------------------	--

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Aspiration hazard : Not classified

CEDRAL TOUCH-UP PAINT 60170

Viscosity, kinematic	1984,127 mm ² /s
----------------------	-----------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)

EC50 other aquatic organisms 1	2954 mg/l Test organisms (species): other aquatic crustacea:Acartia tonsa
--------------------------------	---

(1317-65-3)

LC50 fish 1	> 10000 mg/l
-------------	--------------

EC50 Daphnia 1	> 1000 mg/l
----------------	-------------

Titanium dioxide (13463-67-7)

LC50 fish 2	> 10000 mg/l
-------------	--------------

EC50 other aquatic organisms 1	> 10000 mg/l
--------------------------------	--------------

EC50 72h algae (2)	> 10000 mg/l
--------------------	--------------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Assure that emissions are compliant with all applicable air pollution control regulations. Must follow special treatment according to local regulation.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not established.	Not established.	Not established.	Not established.	Not established.
14.2. UN proper shipping name				
Not established.	Not established.	Not established.	Not established.	Not established.
14.3. Transport hazard class(es)				
Not established.	Not established.	Not established.	Not established.	Not established.
14.4. Packing group				
Not established.	Not established.	Not established.	Not established.	Not established.
14.5. Environmental hazards				
Not established.	Not established.	Not established.	Not established.	Not established.
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not established.

Transport by sea

Not established.

Air transport

Not established.

Inland waterway transport

Not established.

Rail transport

Not established.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not established.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
3(b)	CEDRAL TOUCH-UP PAINT 60170 ; ammonia%	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	ammonia%	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 38 g/l

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

DIRECTIVE 2004/42/EC on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products

EU limit value for CEDRAL TOUCH-UP PAINT 60170 (cat. A/i): 140 g/l

CEDRAL TOUCH-UP PAINT 60170 Contains max 38,00 g/l VOC

15.1.2. National regulations

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : KAOLIN is listed

SZW-lijst van mutagene stoffen : KAOLIN is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.

CEDRAL TOUCH-UP PAINT 60170

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

ETEX France - SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.