

## Traditional Shed Felt Membrane with SBS Modification



Chestershed Mineral SBS is a waterproof protection layer for use on portable type buildings with pitched roofs, such as sheds, stables, kennels and non-inhabited buildings. It features a glass fibre base which is saturated and coated in SBS modified bitumen and finished with light sand on the lower surface and green mineral granules on the upper surface.

When installed in accordance with Chesterfelt's instructions, Chestershed Mineral SBS may be expected to last in excess of 5 years.

### Product Details

| Product Code | Roll Length | Roll Width | Pallet Quantity |
|--------------|-------------|------------|-----------------|
| P147         | 20m         | 1m         | 25 rolls        |

### Key Features & Benefits:

- SBS modified for enhanced flexibility
- Simple nail-on application
- Natural slate green mineral finish
- UV protected
- 5 year life expectancy  
(when fitted to Chesterfelt instructions)

### Mineral Surface Protection

The upper surface of the membrane is protected using mineral granules, which are sourced from natural quarrying. The colours of the minerals therefore can sometimes vary depending on seam depths and extraction positions within the quarry. However, after the effects of the weathering and ageing, any variations will become less visible.

### Installation Guidelines

This product should be installed in accordance with manufacturer recommendations - please consult the Chestershed Application Guide for more details.

## Performance and Key Properties

| Characteristic       | Test Method           | Result | Tolerance |
|----------------------|-----------------------|--------|-----------|
| Roll Length          | BS EN 1848-1          | 20m    | +/- 150mm |
| Roll Width           | BS EN 1848-1          | 1m     | +/- 1.5%  |
| Roll Weight          | BS EN 1849-1          | 40kg   | +/- 5%    |
| Straightness         | BS EN 1848-1          | PASS   |           |
| Visible Defect       | BS EN 1850-1          | PASS   |           |
| Adhesion of Granules | BS EN 12039           | PASS   |           |
| Watertightness       | EN 1928:2000 Method A | PASS   |           |

### Standards

Manufactured in accordance with  
BS EN 13707:2004+A2:2009 - Flexible sheets  
for waterproofing. Reinforced bitumen sheets  
for roof waterproofing.

### Handling and Storage

The material should be stored vertically on a firm flat surface,  
and transported stood on end to avoid damage.

### Certification

UKCA certified & CE Marked to EN 13707:2004+A2:2009.  
CE Certificate Number: 0086-CPR-595938.  
UKCA Certificate Number: 0086 CPR 753192.

### Health and Safety

Health and Safety should be observed at all times in  
accordance with HSE and industry guidance. Specific Risk  
Assessments and Method Statements should be produced by  
contractors where necessary to ensure Working at Heights,  
Fire Safety and Manual Handling rules are compliant with  
current law and regulations. Health and safety data sheets are  
available for all materials on request from Chesterfelt.

### Quality Assurance

Chestershed products are manufactured in accordance with  
BS EN ISO 9001:2015 - Quality Management Systems (QMS).



Cert No.  
0086-CPR-595938



**Chesterfelt Ltd** Foxwood Way, Sheepbridge, Chesterfield, Derbyshire, S41 9RA  
Telephone: 01246 268000 Email: [technical@chesterfelt.co.uk](mailto:technical@chesterfelt.co.uk) Web: [chesterfelt.co.uk](http://chesterfelt.co.uk)



All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out.