

## Declaration of Performance

1. **Product type:** Softwood tongue & groove flooring
2. **Unique Identification:** PTG Timber Floorboards
3. **Intended uses:** Internal domestic use
4. **Manufacturer:** SCA Wood UK, Gibson Lane, Melton Industrial Estate, HU14 3HF
5. **Notified body:** N/A
6. **System of attestation of conformity:** System 4
7. **Declared performance:**

Essential Characteristics	Performance	Harmonised Technical Specification
<b>Reaction to fire – Linked to the minimum mean density and minimum overall thickness</b>	D <sub>fl</sub> -s1 500kg/m <sup>3</sup> Pine (Pinus Sylvestris) 440kg/m <sup>3</sup> Spruce (Picea Abies) 18mm, affixed to substrate without air gap underneath	<b>EN 14342:2013</b>
<b>Release of formaldehyde</b>	E1	
<b>Content of pentachlorophenol</b>	≤ 5 ppm	
<b>Release of other dangerous substances</b>	None used	
<b>Breaking strength</b>	NPD	
<b>Slipperiness</b>	NPD	
<b>Thermal conductivity</b>	0,12 W/(m K) Spruce 0.13 W/(m K) Pine	
<b>Biological durability</b>	DC 4	

The performance of the product identified above is in conformity with this declared performance. This Declaration of Performance is issued under the sole responsibility of the producer identified above.

Signed for and on behalf of the manufacturer by:  
Robert Beardmore, Quality Assurance Manager

Signature

**UK  
CA**