


LIBERTY DRAIN™ 100P

100 mm Wide


Innovative Channel Drainage



LIBERTY DRAIN™ 100P



C 250 Grating



Liberty Slot

Features:

- Manufactured to BS EN 1433 class C 250
- High quality polypropylene channel base
- Interlocking channel tongue & groove joints
- Smooth internal face for rapid flow rates
- Ductile Iron gratings
- 6 mm Safe-slot gratings
- 8 point locking per metre
- Polypropylene edge rail

Options:

- Stepped Falls
- Integrated 90° turns
- Integrated 'T' junctions

Liberty Slot Features:

- Galvanised Steel
- 15 mm Slot Width
- 100 mm Internal Depth
- Suits upto 80 mm deep block paving

Standard Sizes

Code	Int Width (mm)	Invert Depth (mm)	O/all Width (mm)	O/all Depth (mm)	Loading	Waterway (cm ² per grate)	Weight (kg)
LDCP100-6-50	100	71	157	105	C 250	282	12
LDCP100-6-100	100	121	157	155	C 250	282	12
LDCP100-6-150	100	171	157	205	C 250	282	13
LDLS100-15-100	100	121	157	255	C 250	-	11

Sump Unit

Standard Sizes

LDCP100-6-400	100	421	157	441	C 250	282	16
LDLS100-15-500	100	421	157	541	C 250	-	15

