



# SBL200

GALLERY

## PRODUCT INFORMATION

### SBL200

#### Medium Duty Solid Wall Lintel

Cavity: 200-215mm Inner and outer leaves must be suitably tied. **Features**

- We are the only lintel manufacturer to hot-dip galvanize after fabrication providing up to 50% more zinc protection than other approved coatings
- Supergalv coating offers a superior life expectancy
- Post-fabrication galvanizing leaves no surface with inferior paint protection

Length	750-1800	1950-270	2850-300	3150-360	3750-450
		0	0	0	0
L (kN)	20	20	25	40	35
W (kg/m)	9.8	9.8	16.5	16.5	16.5
H (mm)	140	140	222	222	222

(L) Load SWL/UDL value (W) Weight (H) Height

## PRODUCT ATTRIBUTES

Brand	Birtley
Generic Ref	SBL200
Product Range	Solid Wall Lintels
Product Type	Medium Duty Solid Wall Lintel 200-215mm
European Standard/ETA	BS EN845-2:2013+A1:2016
Test Standard	EN846-9:2000/2016
Notified Body	Lucideon Ltd (NB 1289)
Material	Mild Steel S275JR to BS EN10025-2:2004
Coating/Finish/Colour	65µm Hot Dip Galvanized to BS EN ISO 1461:2009
Thermal Performance	Contact us for information
Fire Rating	60 mins (with 2 coat plaster finish)
1. Installation requirement	Bed fully on bricklaying mortar
2. Installation requirement	Must be used with a cavity tray - External walls only
Sales Qty	1
Packaging weight	0
1. Features	Supergalv coating offers superior life expectancy
2. Features	Post-fabrication galvanizing leaves no surface with inferior paint protection
3. Features	Structural grade steel to EN10025
Option 1	Alternative material options: Ultragalv coating (150µm), Stainless Steel 1.4301 (304)
Option 2	Outer Leaf Options: Render mesh (MF)