

Technical Datasheet

Lotrak[®] 80 is a mechanically bonded nonwoven geotextile, with market established technical and hydraulic properties to address every day, industry requirements of separation and filtration. Lotrak[®] 80 is an effective separator beneath selected granular materials and for lining French or narrow trench drains. The main purpose of this geotextile is to prevent the loss of construction aggregates into the underlying soil.

TEST	STANDARD		Lotrak [®] 80
Tensile Strength (kN/m)	EN 10319	Warp	6
		Weft	6
Elongation at max. load (%)	EN 10319	Warp	36
		Weft	42
CBR Puncture Resistance (N)	EN ISO 12236		1050
Cone Drop Penetration (mm)	EN 918		48
Pore size 90% finer than (microns)	EN ISO 12956		128
Water Permeability $V_{I_{H50}}$	EN ISO 11058		0.144
Water Flow Rate (l/m ² /sec)	EN ISO 11058		144
Effect of UV Light	The polypropylene (PP) used contains a UV inhibitor		
Roll Size (m)		Width	4.5
		Length	100



All products are manufactured under BS EN ISO 9001.

Don & Low reserves the right to change specifications or other product information. Don & Low accepts no responsibility or liability for information provided by third parties. No warranties, express or implied, are offered regarding the suitability of any product for your use, as site conditions and customer requirements vary. Should you require further information, please contact us. Products are sold subject to the seller's terms and conditions of sale. No warranty or immunity is offered against infringement of patents or other intellectual property rights. ©Don & Low Limited, 2022. The intellectual property in the products is owned and protected by Don & Low or its licensors.