

**Product Description:**

Walther Strong Utility Duct Tape has a natural rubber adhesive and water-resistant polyethylene backing. It provides easy tear and good conformability. The adhesive has excellent tack and is a great choice for sticking to metal, glass, plastic, sealed concrete and more.

**Product Features:**

- Aggressive natural rubber adhesive provides instant adhesion to a wide variety of surfaces including metal, glass, plastic, and sealed concrete.
- Woven cloth scrim allows the tape to tear easily by hand and provides ease of application and handling.
- Quick repairs, splicing, fast attachments
- Conformable Backing is good for use on contoured surfaces.

**Technical Information Note:**

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

**Typical Physical Properties:**

Colour - Silver and Black, White

Total Tape Thickness - 0.2 mm 8 ml ASTM D3652

Backing - Polyethylene film over cloth scrim

Adhesive Type - Synthetic/Natural Rubber blend

**Typical Performance Characteristics:**

180° Peel Adhesion 8.1 N/cm 74 oz/in ASTM D3330 12 in/min (300 mm/min)

Tensile Strength - 42 N/cm 24 lb/in ASTM D3759

Elongation at Break - 19 % ASTM D3759

**Available Sizes:**

50MMx50M, 75MMx50M

**Property Values:**

Standard Roll Length - 50M

**Handling/Application Information:**

Application Examples -

- Light duty Holding and Bundling applications for a wide variety of materials and substrates.
- Hanging poly-drapes
- Marking and Labelling

Storage and Shelf Life -

- Store under normal conditions of 60°F to 80°F (16°C to 27°C) and 40 to 60% R.H. in the original carton.
- To obtain best performance, use this product within 12 months from date of manufacture.