

## Soudal Scrim Tape

Date: 07/02/2024 – NEW

Page 1 from 1

### Technical data

Warp density	3.6 threads/cm
Weft density	3.6 threads/cm

### Product description

Soudal Scrim Tape is a high quality plasterer's scrim tape.

### Properties

- Fibreglass.
- Excellent strength.

### Applications

- For the jointing of plasterboard panels.
- For covering cracks in walls and ceiling prior to plastering.

### Packaging

*Colours:* white.

*Packaging:* tape roll 90mtr length. Available widths are 48mm and 96mm.

### Shelf life

In unopened packaging in a dry and cool storage at temperatures between +15°C and +25°C: 12 months

### Liability

The content of this technical data sheet is the result of tests, monitoring, and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.