


# Data sheet

Part No.	<b>FXKVR BK</b>
Description	double-walled ducting with draw-wire, halogen-free, low smoke, LSOH  corrugated exterior, smooth interior, including one coupler medium resistance against compression, normal impact resistance
Colour	black, similar to RAL 9005
Fire Behaviour	flame propagating
Classification	N 450
Compression resistance	> 450 N



Standard: EN 61386-1, EN 61386-24, OVE E 8635, OVE E 8635 (ÖNORM E 6517)



Working temperature  
-30 to +70 °C

Art. No.	ED	ID	Bending radius	PU	PU
055107	40 mm	31 mm	230 mm	50 m	1400 m
041925	50 mm	40 mm	310 mm	50 m	-
032332	63 mm	50 mm	350 mm	50 m	-
026353	75 mm	61 mm	350 mm	50 m	-
041343	90 mm	74 mm	400 mm	50 m	-
041344	110 mm	92 mm	462 mm	50 m	-
041990	125 mm	105 mm	500 mm	50 m	-
042514	160 mm	136 mm	650 mm	25 m	-
099585	200 mm	176 mm	750 mm	25 m	-

## Areas of Recommended Application

Area	
Flush mounted (plaster)	False
Surface mounted	False
Suitable for installation on wood	False
Hollow wall	False
Suitable for concrete installation	True
Machine and systems installation	False
Suitable for subsurface installation (screed)	True
Outdoor installation	False
Underground installation	True

## Further technical details

Details	
Model	Pliable
Shape	Outer side ribbed, inner side plain
Surface protection	Untreated
Material	PE-HD