



+44 (0)1327 701910 | sales@hambleside-danelaw.co.uk |

www.hambleside-danelaw.co.uk

# CON6+ DRY RIDGE AND HIP SYSTEM

15 YEAR GUARANTEE

CON6+ is a universal ventilated dry fix ridge and hip system that can be used with all the commonly available ridge and hip tile types. CON6+ can be fitted to all roof pitches\* with no special tools required. The single unique universal jointing gasket adds flexibility and allows compatibility with the most commonly available ridge and hip tile profiles, including baby ridges.

### **FEATURES AND BENEFITS**

- Unique flexible and trimmable patented gasket features weatherproof, continuous integrated water channels and self-sealing detail for the stainless steel fixing screws
- Broader corrugations of the roll membrane edge compliment a variety of ridge tile designs and different roof pitches
- Suitable for ridge and hip tile applications
- Wider butyl strip provides improved and secure
- Stainless steel batten straps included
- Dry fix products eliminate the mortar installation and maintenance issues

## **PACK CONTENTS**

1 x 320mm x 6m Rollflex, 13 x universal gaskets\*, 13 x fixing plates, 13 x 100mm screws, 10 x ridge straps

\* Subject to being used in conjunction with ridge tiles suitable for that pitch



S Fixing plates contain up to 30% recycled impact modified PA 6.6, Universal gaskets contain up to 30% recycled LDPE

### **PRODUCT CODE**

HD CON6

### **TECHNICAL INFORMATION**

- Provides compliance with BS 5250 and BS 5534
- Minimum 5,000mm<sup>2</sup> airflow area per linear metre installed (actual 11,700mm²)
- Suitable for warm and cold roof applications
- Complies with BS 8612
- Patent Application No. GB2402727.8
- Registered design No. GB6349445

COMPONENT	MATERIAL SPECIFICATION
Ridge Fixing Plate	High impact polyamide
Uni-Ridge Tile Gasket	LDPE
Ridge Batten Strap	Stainless Steel
Ridge Screw	Stainless Steel
Rollflex Ridge Roll	Polypropylene fabric with corrugated aluminium edges

# RELATED PRODUCTS



For small interlocking tile cuts on hips and in valleys, code: HD DVC



#### **Hip Tile Support Trays (optional)**

1.65m length, code HDL HT165 3m length, code: HDL HT300



### Vapour Permeable Roofing Underlays Available in four weights, two with optional integral lap tapes and widths of 1.0m or

1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180





