

Ulti-Tile Vents

Description

Extensive range of Interlocking Vent Tiles suitable for five Metric Tile Profiles (TLE; Flat; Double Roman; Double Pantile and Square Top, available in up to five colours, with a 10,000 mm² airflow and can be laid down to 20° roof pitch.

If used for Roof Ventilation for 10,000 mm² space every 1 m for 5,000 mm² space every 2 m.

Guidelines for use

Fitted whilst laying the roof (can be retro fitted as well). Roof membrane needs to be cut to allow penetration into roof space, with membrane folded back over top batten. Can be used in conjunction with Flexi-Pipe ULTI3FP if connection required.

Specifications							
	TLE	Flat	Double Pantile	Double Roman	Square Top	15x9	Flexi-Pipe
Product code	ULTI3TLEV	ULTI3FV	ULTI3DPV	ULTI3DRV	ULTI3STV	ULTI315X9V	ULTI3FP
Free airflow	10,000 mm ²	10,000 mm ²	10,000 mm ²	10,000 mm ²	10,000 mm ²	10,000 mm ²	-
Unit of measure	10/carton	10/carton	10/carton	10/carton	10/carton	10/carton	50/carton
Weight	783 g	811 g	909 g	893 g	906 g	854 g	225 g
Material	Acrylonitrile Styrene Acrylate (ASA) and Polypropylene (PP)						-
Manufacturing process	Injection moulding						-
Colours	Black, Grey, Brown, Red, Terracotta						Black















All products are covered by our 15 year Durability Warranty terms and conditions can be found on our website.



All plastic products are made in UK.



ulti-mate-roofing.co.uk

For more information contact us: 0345 565 3101 | sales@ulti-mate-roofing.co.uk