



INTERLOCKING DRY VERGE SYSTEM

15 YEAR GUARANTEE

The Interlocking Dry Verge System has been manufactured to prevent weather ingress and reliance on mortar at the roof edge. Compatible with most tile profiles, including thin leading edge types, and suitable for use on new build or refurbishment.

FEATURES AND BENEFITS

- Suits all commonly available single lap concrete tiles between 260mm and 355mm batten gauges
- Designed to minimise water run-off staining on the verge and gable wall
- Clip-over design for fast installation
- Dry fix products eliminate the mortar installation and maintenance issues
- Secure single nail fixing when used with optional batten end clip. No special fixings required
- Universal eaves starter unit for all applications and one discreet colour for use with both IDV and TIDV
- Starter unit designed to avoid gutter interference and slotted for ease of adjustment
- Starter unit and ridge cap kits include stainless steel screws and wall plugs
- Universal angle and half-round ridge end cap options with integral ridge closures
- High heat distortion resistance compared to PVC
- UV stabilised for long term performance

PRODUCT OPTIONS



♻️ Slate grey dry verges and ridge caps contains up to 100% recycled PPC

MATERIAL

Polypropylene

PRODUCT CODES AND COLOUR

HD IDV	Verge unit	Black, Slate Grey, Dark Brown, Antique Red, Terracotta
HD TIDV	Thin leading edge verge unit	Black, Slate Grey (available in all standard verge colours to order)
HD IDV/HR	Half-round ridge end cap	Black, Slate Grey, Dark Brown, Antique Red, Terracotta
HD IDV/AR	Angle ridge end cap	Black, Slate Grey, Dark Brown, Antique Red, Terracotta
HD IDV/ST	Starter unit	Black only
HD IDV/BC	Batten End Clip	Galvanised

TECHNICAL INFORMATION

COMPLIES WITH BS 8612

PLEASE SEE
OVERLEAF
FOR TILE
COMPATIBILITY

The HD IDV & TIDV dry verge systems provide a fixing for the verge tiles for use in wind zones 1 to 5* in accordance with BS 8612.

RELATED PRODUCTS



CON6+ Dry Fix Ridge & Hip System
Includes a ventilated membrane with broad corrugated adhesive strips, patented gaskets, stainless steel straps and fixing screws, code: HD CON6



Vapour Permeable Roofing Underlay
Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180



Continuous GRP Verges for Slate
Provides weather protection for slate roof verges. The range allows for a face fixed or under batten fixed solution. Product codes: HDL DV6, DV7, DV8, DV9

* When using flat tiles on the left verge and the tile interlock is not removed, the use as a fixing is limited to zone 3 with a ridge height not exceeding 20m, or zone 4 with a ridge height not exceeding 15m and in urban terrain.

INTERLOCKING DRY VERGE SYSTEM COMPATIBILITY

CREST	
Double Pantile	IDV
Double Roman	IDV
Planum	IDV
V10	MV20

FORTICRETE	
Gemini	IPTDV
Minislate	IPTDV
Senator	IDV
SL8	TIDV
V2	IDV

EDILIANS	
Alpha 10	IDV⁽⁴⁾
Arboise	MV20
Beauvoise	MV20
HP10	IDV⁽³⁾
HP17	IDV⁽²⁾

BREEDON	
Double Roll	IDV
Elite	TIDV
Flat	IDV
Square Top	IDV

MARLEY	
Anglia Plus	IDV
Ashmore	IPTDV
Duo Modern	IDV
Double Roman	IDV
Edgemere	TIDV
Ludlow Major	IDV
Ludlow Plus	IDV
Malvern	IDV
Marquess	MV20
Mendip	IDV
Modern	IDV
Monarch	MV20
Wessex	IDV

BMI (REDLAND)	
Cambrian	MV20
Double Roman	IDV
Duo Plain	IPTDV
Fenland	IDV
Grovebury	IDV
Landmark Double Pantile	IDV
Landmark Slate 10	TIDV
Mini Stonewold	IDV
Norfolk Pantile	IDV
Regent	IDV
Renown	IDV
Richmond	TIDV
Richmond 10	TIDV
Saxon 10	TIDV
Stonewold MKII	IDV



RUSSELL	
Argyll	IDV
Bute	TIDV⁽²⁾
Cheviot	IDV
Derwent	IDV
Double Roman	IDV
Galloway	TIDV
Grampian	IDV
Highland	IDV
Lothian	TIDV
Moray	TIDV
Pennine	IDV
Polden	TIDV

WIENERBERGER (SANDTOFT)	
20/20	MV20
Balmoral	MV20
Britlock	MV20⁽¹⁾ TIDV⁽⁵⁾
Calderdale Edge	IDV
Calderdale Slate	IDV
Cassius	TIDV
Double Pantile	IDV
Double Roman	IDV
Dual Calderdale	IDV
Dual TLE	TIDV
Lindum	IDV
Olympus	IDV
Neo Pantile	IDV
Rivius	TIDV
Shire Pantile	IDV
Standard Pattern	IDV
TLE	TIDV

MANNOK (QUINN)	
Devenish	TIDV
Locherne	IDV
Rathmore	TIDV
Western Slate	IDV

DOUBLE LAP TILES	
Plain Tiles	INVERG

- ¹ Batten gauge 240 to 260mm
² Down to batten gauge 260mm
³ Batten gauge 330 to 355mm
⁴ Batten gauge 330 to 355mm
⁵ Batten gauge 260 to 285mm with continuous verge batten



♻️ Slate grey dry verges and ridge caps contains up to 100% recycled PPC

