

ROOF TILES

Tile Range



Thin Flat Tile	
Size	Thickness
420mm x 334mm	21mm
Weight	Minimum Headlap*
4.7kg	75mm (normal exposure)
Minimum Pitch*	Maximum Gauge
100mm headlap - 17.5°	345mm
75mm headlap - 22.5°	Covering Capacity
Cover Width	75mm headlap -
305mm	9.7 tiles/m²
Weight of Tiling	100mm headlap -
75mm headlap -	10.5 tiles/m²
45kg/m²	Nail Size
100mm headlap -	40mm x 3.35mm
49kg/m²	Batten Size
	Aluminium Alloy
Tiles per Band	Tiles per Pallet
38	228
	Weight of Pallet
	1086kg



Duo Thin Flat Tile	
Size	Thickness
420mm x 334mm	21mm
Weight	Minimum Headlap*
4.7kg	75mm (normal exposure)
Minimum Pitch*	Maximum Gauge
100mm headlap - 17.5°	345mm
75mm headlap - 22.5°	Covering Capacity
Cover Width	75mm headlap -
305mm	9.7 tiles/m²
Weight of Tiling	100mm headlap -
75mm headlap -	10.5 tiles/m²
45kg/m²	Nail Size
100mm headlap -	40mm x 3.35mm
49kg/m²	Batten Size
	Aluminium Alloy
Tiles per Band	Tiles per Pallet
38	228
	Weight of Pallet
	1086kg



Round Top Tile	
Size	Thickness
420mm x 334mm	26mm
Weight	Minimum Headlap
4.5kg	75mm
Minimum Pitch	Maximum Gauge
75mm headlap - 15°	345mm
Cover Width	Covering Capacity
305mm	75mm headlap -
Weight of Tiling	9.8 tiles/m²
75mm headlap -	100mm headlap -
47kg/m²	10.6 tiles/m²
100mm headlap -	Nail Size
51kg/m²	70mm x 3.35mm
Batten Size	Aluminium Alloy
50 x 25mm (rafters not exceeding 600mm c/c)	Tiles per Pallet
	210
Tiles per Band	Weight of Pallet
35	960kg



Square Top Tile	
Size	Thickness
420mm x 330mm	25mm
Weight	Minimum Headlap
4.6kg	75mm above 25°
Minimum Pitch	Maximum Gauge
22.5°	345mm
Cover Width	Covering Capacity
297mm	75mm headlap -
Weight of Tiling	9.8 tiles/m²
75mm headlap -	100mm headlap -
45kg/m²	10.5 tiles/m²
100mm headlap -	Nail Size
49kg/m²	55mm x 3.35mm
Batten Size	Aluminium Alloy
50 x 25mm (rafters not exceeding 600mm c/c)	Tiles per Pallet
	216
Tiles per Band	Weight of Pallet
36	995kg




COMING Q4 2024

ROOF ACCESSORIES

Multi Ridge Tiles

Length x Width	457mm x 250mm
Weight	5kg
Maximum Roof Pitch	45°
Tiles per pallet	140



Hip End Tile

Length	510mm
Width	260mm
Height	130mm
Thickness	25mm
Weight	6.4kg
Colours Available	Anthracite & Terracotta



EMAIL PLANS TO
ROOFING@FPMCCANN.CO.UK

COLOURS

Available in 6 Colours



✓ 48 Hour lead time on all estimates
✓ All size enquiries welcome, no matter the size

VENTILATION PRODUCTS

Underlay

FP McCann 150gsm Vapour Permeable Membrane

High performance breather membrane
3 layer membrane
Suited for all wind zones
Tested to BS5534:2014 +A2:2018 wind loading
Supplied via partnership with Permavent

Eaves Vent System 6m

Roll Out Rafter Eave Vent 300mm x 6m

Felt Support Tray x10

Over Fascia Ventilator 10mm or 25mm x6

The Eaves Vent System 6m is available as either a 2 part or 3 part system providing a 10mm or 25mm ventilation gap.

McCannVent

Free ventilation area
10,000mm²

Minimum Pitch
22.5°

Profiles Available
Thin Flat and Round Top

Recommended Tile Spacing
5mm gap - 2m centres
10mm gap - 1m centres

Colours Available
Anthracite, Grey, Terracotta, Brown

DRY FIX SYSTEMS

McCannFast Ridge & Hip Kit 6m

McCannFast Ridge Roll 6m Ventilated or Unventilated

100mm x M5 S/S Screw x10

McCannFast Ridge Union x10

McCannFast Union Clip x10

Ridge Batten Connector x10

Dry Fix Valley System

Eaves Closure Piece

Top Closure Piece 90°

GRP Dry Fix Valley Trough 3m

Minimum Pitch: As per tile profile Maximum Pitch: 60° All components available with a 70mm or 110mm upstand

Dry Verge System

Dry Verge Unit

Multi Ridge End Cap

FIXINGS AND CLIPS

Tile Fixings

