

## Combi Drill LXT®

# DHP484Z

18V • 54 Nm • 0 – 2 000 min<sup>-1</sup>

**A powerful, brushless general-use impact drill for screwdriving and drilling**

An efficient, brushless drill for professional screwdriving and drilling with or without hammer action, two power settings. Max. torque of 54 / 30 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Tool only, battery and charger not included.



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 500 / 2000 min <sup>-1</sup>
Max. fastening torque Hard/Soft	54 / 30 Nm
Torque setting	21
Impacts per Minute (IPM)	0 - 7500 / 30000 min <sup>-1</sup>
Max. Drilling Diameter in Wood	38 mm
Drilling Capacity Wood (Auger Bit)	38 mm
Drilling Capacity Wood (Self-feed bit)	76 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Concrete	13 mm
Max. Drilling Diameter in Steel	13 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Electronic brake	✓

### User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low
- Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque
- Electric brake for maximum productivity and increased operator safety
- Reversing switch is conveniently located

**EAN 0088381826105**

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## Standard AC

**251314-2**

Truss Head Screw M4\*12, Td140D



**346317-0**

Belt Hook



**784637-8**

Screw Bit, Ph2 – S6, 45 Mm, Double



## Optional AC

**196311-0**

Keyless Drill Chuck, 13 mm



**784637-8**

Screw Bit, Ph2 – S6, 45 Mm, Double



**D-72877**

Drill bit set T.C.T, 5 pcs



## Other

[User manual](#)

[Parts drawing](#)