

GAS FRAMING NAILER



CAPABLE
OF FIRING
NAIL SCREWS

360Xi

TOOL PRODUCT CODE:
019700

The 360Xi framing nailer is light and perfectly balanced to guarantee a great performance for multiple applications. A high performing lithium battery and a weatherproof fuel cell ensures the tool will run all day, every day no matter the challenge.

IDEAL USERS

Carpenter, Roofer or General Builder working on New Build projects such as large housing developments.



FEATURE



BENEFIT

- | | |
|---|---|
| <ul style="list-style-type: none"> Unbeatable power to weight ratio, the most powerful Paslode framing nailer: 105 Joules Light and perfectly balanced with a re-engineered grip and new battery position Quick release magazine Fast charging, high performing Lithium battery (200 shots in just 2 minutes) Cold weather performance | <ul style="list-style-type: none"> Able to drive 90mm Ring Shank nails into the hardest substrates Ensures extra comfort and convenience with reduced fatigue, guaranteeing all day productivity Designed to eliminate nail jams Delivers up to 13,000 shots per charge, equates to over 5 nail fuel packs Allows user to work down to -15°C |
|---|---|
- Easy to use rotating depth of drive adjuster
- Allows optimal embedment of nails for a clean, flush finish

APPLICATIONS

- | | | |
|---|--|--|
| <ul style="list-style-type: none"> Roof battening Trusses assembly Roof boarding Cladding Timber frame | <ul style="list-style-type: none"> Stud work Flat roofing Overboarding Floor boarding Panelling | <ul style="list-style-type: none"> Chipboard Formwork Decking Packaging Steel tiles fastening |
|---|--|--|



CONSUMABLES

EN ISO11148-13
European
Safety
Standard

BS 5534
British Standard

EUROCODE 5 SERVICE CLASS

All Paslode framing nails are classified according to Eurocode 5 Service Class 1, 2 and 3 providing a suitable nail for every application.

- Requires Paslode 2.8 or 3.1mm RoundDrive® nails. Available in sizes from 50 - 90mm
- Smooth or Ring Shank nails are available

NAIL SELECTION GUIDE

														
NAIL	FUEL CELLS	QTY	CODE	APPLICATIONS										
				Floor boarding	Stud work	Noggin	Joist	Timber frame	Roof battening	Close boarding	Roof decking	Decking	External cladding	Fencing
51 x 2.8mm Ring	3	3300	141083	●										
63 x 2.8mm Ring	3	3300	141078	●										
75 x 3.1mm Ring	2	2200	141081		●	●								
90 x 3.1mm Smooth	2	2200	141076		●	●	●							
90 x 3.1mm Ring	2	2200	141082		●	●								
50 x 2.8mm NailScrew*	1	1250	142100								●			●
51 x 2.8mm Ring	3	3300	141075								●			
51 x 2.8mm Ring	1	1100	141080											
63 x 2.8mm Ring	3	3300	141071	●							●			
63 x 2.8mm Ring	1	1100	141079	●							●			
63 x 3.1mm Ring	1	1100	141089							●				
63 x 3.1mm Ring	2	2200	141073											
65 x 2.8mm NailScrew*	1	1250	142102	●							●		●	
75 x 2.8mm NailScrew*	1	1250	142104								●		●	
75 x 3.1mm Ring	2	2200	141072		●	●	●	●						
90 x 3.1mm Smooth	2	2200	141070						●					
90 x 3.1mm Smooth	1	1100	141077						●					
90 x 3.1mm Ring	2	2200	141074						●					
63 x 2.8mm Ring	3	3750	142014							●		●		
63 x 3.1mm Ring	2	2200	140625							●				
75 x 3.1mm Ring	2	2200	140630							●		●		
90 x 3.1mm Smooth	2	2500	142039					●	●					
90 x 3.1mm Ring	2	2500	142040		●	●			●					
50 x 2.8mm NailScrew A2	1	1250	142101								●		●	●
51 x 2.8mm Ring A2	1	1100	140624										●	●
63 x 2.8mm Ring A2	1	1100	140626									●		
65 x 2.8mm NailScrew A2	1	1250	142103								●		●	●
75 x 2.8mm NailScrew A2	1	1250	142105								●		●	●
80 x 3.1mm Ring A2	1	1100	140627									●		

*ELECTRO GALV ≥ 12µm

- BRIGHT (INDOOR, SERVICE CLASS 1.)
- ELECTRO GALV ≥ 12µm / GALV-PLUS® ≥ 15µm (INDOOR NOT HEATED, OUTDOOR PROTECTED, SERVICE CLASS 2.)
- HOT DIPPED GALV (OUTDOOR, EXPOSED TO WEATHER, SERVICE CLASS 3.)
- STAINLESS STEEL A2-304 / A4-316 (OUTDOOR, EXPOSED TO WEATHER, SERVICE CLASS 3.)

All Paslode nails are hexavalent chromium, cadmium and lead free. Technical documentation available via the website - www.paslode.co.uk



DID YOU KNOW:

The Paslode No-mar Cladding probe is available as an interchangeable accessory. Product Code: 019783



BATTERY PRODUCT CODE:
018880

FUEL CELL PRODUCT CODE:
300348

ACCESSORIES

DESCRIPTION	QTY	CODE
SERIES-i Fuel Cell Blister Pack (Pack of 1)	1	300348
360Xi No-Mar Cladding Probe	1	019783
IM360Ci No-Mar Cladding Probe	1	013211



www.paslode.co.uk

Follow us on @PaslodeUK

Customer Service: 0800 833 381