

GAS FRAMING NAILER



IM350+

TOOL PRODUCT CODE:
906500

The **NEW** and improved version of the iconic IM350+ tool heralds the seventh generation of Paslode gas nailing technology. Benefitting from 40 years of customer insight and innovation, the tool is strong and durable, guaranteeing tool performance and reliability.

IDEAL USERS

Carpenter, Roofer or General Builder working on New Build and Renovation projects.



FEATURE



BENEFIT

- | | |
|--|--|
| ● Powerful Paslode framing nailer: 82 Joules | ● Suitable for versatile framing applications |
| ● Longer fan run time | ● Improved tool cooling with longer fan cycle for rapid firing |
| ● New rubberized grip for improved handling and feel | ● Added comfort and control for improved ergonomics and manoeuvrability |
| ● Fast charging, high performing Lithium battery (200 shots in just 2 minutes) | ● Delivers up to 9,000 shots per charge, equates to over 4 nail fuel packs |
| ● Bigger battery notch | ● Easier battery insertion and removal |

APPLICATIONS

- | | |
|------------------|------------------|
| ● Roof battening | ● Flat roofing |
| ● Truss work | ● Overboarding |
| ● Timber frame | ● Floor boarding |
| ● Cladding | ● Panelling |
| ● Stud work | ● Shuttering |
| ● Joists | ● Decking |
| ● Roof boarding | ● Hoarding |



CONSUMABLES

EN ISO11148-13
European
Safety
Standard

BS 5534
British Standard

EUROCODE 5 SERVICE CLASS

All Paslode framing nails are classified according to Eurocode 5 Service Class 1, 2 and 3 providing a suitable nail for every application.

- 2.8 or 3.1mm clipped nail available in sizes from 50 - 90mm
- Smooth or Ring Shank nails are available
- Wide range of Paslode Nail fuel packs available

NAIL SELECTION GUIDE

NAIL	FUEL CELLS	QTY	CODE	APPLICATIONS									
				Floor boarding	Stud work	Noggin	Joist	Timber frame	Roof battening	Close boarding	Roof decking	Decking	External cladding
51 x 2.8mm Ring	3	3300	141202	●									
63 x 2.8mm Ring	3	3300	141208	●									
75 x 3.1mm Ring	2	2200	141226		●	●							
90 x 3.1mm Smooth	2	2200	141233		●	●	●						
51 x 2.8mm Ring	3	3300	141204							●			
51 x 2.8mm Ring	1	1100	141256							●			
63 x 2.8mm Ring	3	3300	141210		●					●			
63 x 2.8mm Ring	1	1100	141259		●					●			
63 x 3.1mm Ring	1	1100	141273						●				
63 x 3.1mm Ring	2	2200	141221						●				
75 x 3.1mm Ring	2	2200	141227		●	●	●	●					
90 x 3.1mm Smooth	2	2200	141234				●						
50 x 2.5mm Ring	2	2200	141200	Black hardened full head nail for metal roofing applications									
51 x 2.8mm Ring	3	3300	141205										
63 x 2.8mm Ring	3	3300	141211						●		●		●
63 x 3.1mm Ring	2	2200	141222						●		●		
75 x 3.1mm Ring	2	2200	141228						●				
75 x 3.1mm Ring	1	1100	141265						●				
90 x 3.1mm Smooth	2	2200	141235				●	●					
90 x 3.1mm Smooth	1	1100	141267				●	●					
90 x 3.1mm Unilock	2	2200	141236		●	●	●	●					
51 x 2.8mm Ring A2	1	1100	141257							●		●	●
63 x 2.8mm Ring A2	1	1100	141261							●			
80 x 3.1mm Ring A2	1	1100	141266								●		

- BRIGHT (INDOOR, SERVICE CLASS 1.)
- ELECTRO GALV ≥ 12µm / GALV-PLUS® ≥ 15µm (INDOOR NOT HEATED, OUTDOOR PROTECTED, SERVICE CLASS 2.)
- HOT DIPPED GALV (OUTDOOR, EXPOSED TO WEATHER, SERVICE CLASS 3.)
- STAINLESS STEEL A2-304 / A4-316 (OUTDOOR, EXPOSED TO WEATHER, SERVICE CLASS 3.)

All Paslode nails are hexavalent chromium, cadmium and lead free.

Technical documentation available via the website - www.paslode.co.uk



DID YOU KNOW:

- 1 lithium battery is compatible for 8 Paslode tools.



BATTERY PRODUCT CODE:
018880

FUEL CELL PRODUCT CODE:
300346

ACCESSORIES

DESCRIPTION	QTY	CODE
IM350 / IM350+ Standard Fuel Cell Blister Pack Pink (Pack of 2)	1	300346
No-mar Work Contact Element Adaptor Kit - (Butterfly Clip Depth of Drive)	1	012082



Follow us on @PaslodeUK

www.paslode.co.uk

Customer Service: 0800 833 381