



HDX150

GALLERY

PRODUCT INFORMATION

HDX150

Extra Heavy Duty Cavity Wall Lintel

Cavity: 150-165mm Outer Leaf: 100mm Inner Leaf: 100mm **Must have a solid, fully jointed blockwork infill to inner leaf.** **Features**

- Supergalv coating offers superior life expectancy
- Post-fabrication galvanizing leaves no surface with inferior paint protection
- Birtley lintels have been tested to BS 476-20:1987 to determine the fire resistance

Length	750-2100	2550-3300	3450-4200	4350-4800	4950-5100
L (kN)	100	80	70	60	45
W (kg/m)	24	24	24	24	24
H (mm)	236	236	236	236	236

(L) Load SWL/UDL value (W) Weight (H) Height

PRODUCT ATTRIBUTES

Brand	Birtley
Generic Ref	HDX150
Product Range	Cavity Wall Lintels
Product Sub-range	150-165mm Cavity
Product Type	Extra Heavy Duty Cavity Wall Lintel - 100mm Inner leaf/100mm Outer Leaf
European Standard/ETA	BS EN845-2:2013+A1:2016
Test Standard	EN846-9:2000/2016
Notified Body	Lucideon Ltd (NB 1289)
Material	Mild Steel S275JR to BS EN10025-2:2004
Coating/Finish/Colour	65µm Hot Dip Galvanized to BS EN ISO 1461:2009
Thermal Performance	Contact us for information
Insulation	Expanded Polystyrene - BREEAM rating A+
Fire Rating	60 mins (with 2 coat plaster finish)
1. Installation requirement	Bed fully on bricklaying mortar
2. Installation requirement	Must be used with a cavity tray - External walls only
3. Installation requirement	Not suitable for point loads or concrete floors
4. Installation requirement	150mm Minimum end bearing
Sales Qty	1
Packaging weight	0
1. Features	Supergalv coating offers superior life expectancy
2. Features	Post-fabrication galvanizing leaves no surface with inferior paint protection
3. Features	Lack of baseplate and factory fitted insulation reduces thermal bridging
4. Features	Structural grade steel to EN10025
5. Features	Plaster key to inner leaf
Option 1	Alternative material options: Ultragalv coating (150µm), Stainless Steel 1.4301 (304)
Option 2	Outer Leaf Options: Reduced length flange (RFF), No rainwater drip (ND), Render mesh (MF)
Option 3	Inner Leaf Options: No plaster key (NM), Closer plate (CP)