




CB90

GALLERY



PRODUCT INFORMATION

CB90

Standard Duty Cavity Wall Lintel

Cavity: 90-105mm Outer Leaf: 100mm Inner Leaf: 100mm **Not suitable for point loads or concrete floors.** **Features**

- We are the only lintel manufacturer to hot-dip galvanize after fabrication providing up to 50% more zinc protection than other approved coatings.
- Supergalv coating offers superior life expectancy
- Our standard cavity lintels deliver up to 55% improvement on SAP default value in thermal bridging.

Length	750-1200	1200-1350	1500-1650	1800-2100	2250-2400	2500	2700-3000	3150-3900
L (kN)	15	15	15	20	22	26	26	26
W (kg/m)	5.8	5.9	7.3	8.3	10.1	10.9	11.8	14.4
H (mm)	97	102	102	132	141	157	181	197

(L) Load SWL/UDL value (W) Weight (H) Height

PRODUCT ATTRIBUTES

Brand	Birtley
Generic Ref	CB90
Product Range	Cavity Wall Lintels
Product Sub-range	90-105mm Cavity
Product Type	Standard Duty Cavity Wall Lintel - 100mm Inner leaf/100mm Outer Leaf

European Standard/ETA	BS EN845-2:2013+A1:2016
Test Standard	EN846-9:2000/2016
Notified Body	Lucideon Ltd (NB 1289)
Material	Mild Steel S275JR to BS EN10025-2:2004
Coating/Finish/Colour	65µm Hot Dip Galvanized to BS EN ISO 1461:2009
Thermal Performance	Contact us for information
Insulation	Expanded Polystyrene - BREEAM rating A+
Fire Rating	60 mins (with 2 coat plaster finish)
1. Installation requirement	Bed fully on bricklaying mortar
2. Installation requirement	Must be used with a cavity tray - External walls only
3. Installation requirement	Not suitable for point loads or concrete floors
4. Installation requirement	150mm Minimum end bearing
Sales Qty	1
Packaging weight	0
1. Features	Supergalv coating offers superior life expectancy
2. Features	Post-fabrication galvanizing leaves no surface with inferior paint protection
3. Features	Lack of baseplate and factory fitted insulation reduces thermal bridging
4. Features	Structural grade steel to EN10025
5. Features	Plaster key to inner leaf
Option 1	Alternative material options: Ultragalv coating (150µm), Stainless Steel 1.4301 (304)
Option 2	Outer Leaf Options: Reduced length flange (RFF), No rainwater drip (ND), Render mesh (MF)
Option 3	Inner Leaf Options: No plaster key (NM), Closer plate (CP)