



CBEV90

GALLERY



PRODUCT INFORMATION

CBEV90

Standard Duty 90mm Cavity Wall Eaves Lintel

Must be propped during installation to achieve loads. Requires fully bonded masonry and a continuous wall plate. **Features**

- We are the only lintel manufacturer to hot-dip galvanize after fabrication providing up to 50% more zinc protection than other approved coatings.
- Lack of baseplate and factory fitted insulation reduces thermal bridging
- On top of our industry-leading performance, you'll also enjoy the unlimited support of our entire technical team, free of charge.

Length	750-2100	2250-2700	2850-3000	3150-3900
L (kN)	20	20	18	18
W (kg/m)	8.3	12	11.5	14
H (mm)	162	174	190	206

(L) Load SWL/UDL value (W) Weight (H) Height

PRODUCT ATTRIBUTES

Brand	Birtley
Generic Ref	CBEV90
Product Range	Cavity Wall Eaves Lintels
Product Sub-range	90-125mm Cavity
Product Type	Eaves Duty Cavity Wall Lintel - 100mm Inner Leaf

European Standard/ETA	BS EN845-2:2013+A1:2016
Test Standard	EN846-9:2000/2016
Notified Body	Lucideon Ltd (NB 1289)
Material	Mild Steel S275JR to BS EN10025-2:2004
Coating/Finish/Colour	65µm Hot Dip Galvanized to BS EN ISO 1461:2009
Thermal Performance	Contact us for information
Insulation	Expanded Polystyrene - BREEAM rating A+
Fire Rating	60 mins (with 2 coat plaster finish)
1. Installation requirement	Bed fully on bricklaying mortar
2. Installation requirement	Must be used with a cavity tray - External walls only
3. Installation requirement	Requires fully bonded masonry and a continuous wall plate
4. Installation requirement	150mm Minimum end bearing
Sales Qty	1
Packaging weight	0
1. Features	Supergalv coating offers superior life expectancy
2. Features	Post-fabrication galvanizing leaves no surface with inferior paint protection
3. Features	Lack of baseplate and factory fitted insulation reduces thermal bridging
4. Features	Structural grade steel to EN10025
5. Features	Plaster key to inner leaf
Option 1	Alternative material options: Ultragalv coating (150µm), Stainless Steel 1.4301 (304)
Option 2	Outer Leaf Options: Reduced length flange (RFF), No rainwater drip (ND), Render mesh (MF)
Option 3	Inner Leaf Options: No plaster key (NM), Closer plate (CP)