

AQUAPOL

EMERGENCY REPAIR

★ ★ ★
**GREAT
PERFORMANCE
IN EXTREME
CONDITIONS**
★ ★ ★



INSTANT WATERPROOF COATING FOR ROOFS

IMMEDIATE WATERPROOFING

BRUSH APPLIED

ONE COAT APPLICATION

NO PRIMER REQUIRED

FOR WET OR DRY SURFACES



CLEAN



BRUSH ON



**INSTANTLY
WATERTIGHT**

EAGLE AQUAPOL EMERGENCY REPAIR

AQUAPOL ROOF compound is a single application fibre-reinforced all weather acrylic coating that provides a tough yet flexible seamless membrane for the long term protection of industrial & domestic roofs. It can even be applied in damp weather conditions where it will resist water wash-off and cures to produce a water impermeable membrane. An immediate, effective economical solution for the remedial repair of roofs. Suitable for use on concrete, fibre/cement, metal, felt, mastic, asphalt and existing bituminous coatings, leadwork, slates, tiles & brickwork. waterproofs gutters (plastic & metal), rigid pvc, downpipes, gulleys, flashing, vents, corrugated iron, copper and zinc.



PREPARATION

- > As with all surface coatings, preparation of the surface is of great importance and will influence the degree of adhesion obtained and the life of the coating.
- > Ensure surfaces are structurally sound, clean, free from dust, loose debris, algae and any contaminants and free from standing water.
- > Repair all cracks, splits & grazed areas. Fill holes and imperfections with Eagle's Bitumen Mastic.
- > Stick down loose felt with Eagle's felt adhesive. Blisters in felt must be cut, dried, re-bonded and sealed.
- > Do not use on XPS or pvc foil or in areas where subsequent solvent or oil contact is likely.

APPLICATION

- > Ensure product is stirred thoroughly before use.
- > Apply by brush straight from container in a single uniform application rate of 1-2 kg per m².
- > In extreme cases a second coat may be applied 2-3 days after initial application.

COVERAGE

- > 1-2 kg per m² when applied as directed.

STORAGE

- > Store unopened in original container in a cool dry place within 5°C-25°C, out of direct sunlight and sources of ignition protect from frost. Keep away from sources of ignition for transportation purposes ensure that product is upright and the lid fully closed.

SHELF LIFE

- > Storage life 12 months in tightly sealed undamaged containers.

IMPORTANT

- > Contains a flammable solvent, and all normal precautions against fire must be taken during both storage and use. Keep away from sources of ignition.

CLEANING

- > Clean tools and equipment with white spirit.



AQUAPOL
EMERGENCY REPAIR

EAGLE

Tel: +44(0) 3304 004170
info@eagle-insulations.com
www.eagle-insulations.com