

Product Specification of Kingspave Cobble

Capture the elegance of nostalgic old world charm, the Kingspave Cobble paving collection has a gently distressed surface to achieve that natural weathered appearance.

Feature: 3 Size Mix. Each pack contains the 3:2:1 ratio eliminating the need for multipacks. Each slice within a pack contains 1sqm so no need to split packs.

Thickness: 60mm

Use: Driveways & Footpaths— domestic & commercial Laying Patterns: 3 Size Mix layout

Spacing Nibs: 1.5mm nibs

Finishes & Colour: Tumbled finish with 10 colour options Kerbs: Complimentary kerb range available



Walnut



Sycamore



Silver Grey



Oak



Mulberry



Damson



Maple



Juniper



Chestnut



Birch

	Brick Size (mm)	Colours	No.per Sq.m	No.Per Pack	m2 per Slice	Pack Size m2	Pack Weight Kgs	No. Packs per Artic	m2 per Artic Load
3 Size mix	225x150x60	Maple, Damson, Sycamore, Chestnut, Birch, Mulberry, Walnut, Juniper, Silver Grey, Oak	17	136	1	8	1100	25	200
	150x150x60		14	112	-	-	-	-	
	112.5x150x60		6	48	-	-	-	-	
Single Size	225x150x60	Maple, Damson, Sycamore, Chestnut, Birch, Mulberry, Walnut, Juniper, Silver Grey, Oak	29.63	250	1.68	8.43	1160	24	202.5

Raw Materials: Sand, Stone, Cement, Pigment

Manufacturing Process: Hydraulically Pressed

Manufacturing Standards: Manufactured to BS EN 1338

Quality Systems: All products undergo testing to standards of EN ISO 9001 and are covered by CE certification.

Application: Please refer to Health & Safety data sheets Installation: Installed to BS 7533-3

Performance Criteria: Strength: >3.6MPa or 250N/mm