

# PADSTONE DATA SHEET



<b>Strength Class</b>	C40/50
<b>Water Cement Ratio</b>	0.34
<b>Nominal Plastic Density</b>	2392 ± 100 kg/m <sup>3</sup>
<b>Consistence Class</b>	S1 (0-60mm)
<b>Cement Type</b>	CEM II/B-V + SR 42.5N
<b>Total Chloride ion by weight of cement</b>	0.12%
<b>Total Sulphate by weight of cement</b>	3.00%
<b>Total Alkali</b>	2.549kg/m <sup>3</sup>
<b>Compressive Strength</b>	50N/mm <sup>2</sup>

Note :Padstones can be laid in any orientation

Length (mm)	Height (mm)	Width (mm)	Weight (kg)	Pack No.
600	215	100	32	24
600	140	100	21	24
440	440	215	100	48
440	215	215	51	48
440	215	140	31	48
440	215	100	22	48
440	140	140	22	48
440	140	100	15	48
380	140	215	29	48
330	215	100	18	48
300	100	215	15	48
300	100	140	10	48
300	300	215	45	48
215	215	440	48	48
215	215	140	15	48
215	215	100	11	48
215	140	600	45	48
215	140	100	7	48
L SHAPED 440	215	100	41	24
L SHAPED 300	215	100	26	24



Please confirm stock availability and any special sizes with the Cadeby sales office 01455 290780

