

## Traditional Waterproofing Membrane for Non-Habitable Buildings



Trade Top is a traditional bitumen roofing membrane for use on all types of non-habitable dwellings and outbuildings. It features a glass fibre base which is saturated and coated in high quality bitumen and finished with light sand on the lower surface and green mineral granules on the upper surface.

### Product Details

Product Code	Roll Length	Roll Width	Pallet Quantity
P119	10m	1m	30 rolls

### Key Features & Benefits:

- Cost-effective
- Heavy grade
- Green Mineral Finish
- UV protected

### Suitability

To complete a full system, Trade Top is fitted above the underlay membrane and is used as the final waterproofing layer. When used as part of a multi-layer built up roofing system, it provides reliable waterproofing protection and is suitable for use on a wide range of buildings.

### Installation Guidelines

This product should be installed in accordance with manufacturer recommendations and all relevant national standards and codes of practice, including BS 8217:2005 – the code of practice for reinforced bitumen membranes for roofing.

### Mineral Surface Protection

The upper surface of the membrane is protected using mineral granules, which are sourced from natural quarrying. The colours of the minerals therefore can sometimes vary depending on seam depths and extraction positions within the quarry. However, after the effects of the weathering and ageing, any variations will become less visible.

## Performance and Key Properties

Characteristic	Test Method	Result	Tolerance
Roll Length	BS EN 1848-1	10m	+/- 150mm
Roll Width	BS EN 1848-1	1m	+/- 1.5%
Roll Weight	BS EN 1849-1	29kg	+/- 5%
Straightness	BS EN 1848-1	PASS	
Visible Defect	BS EN 1850-1	PASS	
Adhesion of Granules	BS EN 12039	5.43%	<20%
Watertightness	EN 1928:2000 Method A	PASS	

## Maintenance and Repair

Routine inspection, cleaning and maintenance of the roof membranes should be based on the recommendation in BS 8217:2005. Should it be damaged either during construction or at later date, then the repairs should be made using the same materials so that the performance of the built-up membranes is retained.

## Standards

Manufactured in accordance with  
BS EN 13707:2004+A2:2009 - Flexible sheets  
for waterproofing. Reinforced bitumen sheets  
for roof waterproofing.

## Handling and Storage

The material should be stored vertically on a firm flat surface  
and transported stood on end to avoid damage.

## Certification

UKCA certified & CE Marked to EN 13707:2004+A2:2009.  
CE Certificate Number: 0086-CPR-595938.  
UKCA Certificate Number: 0086 CPR 753192.

## Health and Safety

Health and Safety should be observed at all times in  
accordance with HSE and industry guidance. Specific Risk  
Assessments and Method Statements should be produced by  
contractors where necessary to ensure Working at Heights,  
Fire Safety and Manual Handling rules are compliant with  
current law and regulations. Health and safety data sheets are  
available for all materials on request from Chesterfelt.

## Quality Assurance

Trade Top is manufactured in accordance with BS EN ISO  
9001:2015 - Quality Management Systems (QMS).



Cert No.  
0086-CPR-595938



**Chesterfelt Ltd** Foxwood Way, Sheepbridge, Chesterfield, Derbyshire, S41 9RA  
Telephone: 01246 268000 Email: [technical@chesterfelt.co.uk](mailto:technical@chesterfelt.co.uk) Web: [chesterfelt.co.uk](http://chesterfelt.co.uk)



All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out.