

easy-trim 

SPECIAL 1

WHATEVER THE WEATHER

easy-trim

SPECIAL 1

WHATEVER THE WEATHER

Easy-Trim Special 1 is a single component liquid membrane which is fast-curing, free of solvent and UV stable.

Can be applied on wet or dry surfaces, which are free of dust, grease, oil, loose parts and standing water.

- Can be applied in wet conditions - no more lost days due to wet weather
- Suitable for use on the majority of substrates.
- Fully UV stable unlike other products on the market.
- Can be applied on to damp surfaces - will resist standing water.
- Simple & efficient one-coat system.
- Single component liquid membrane - no need for additional accelerators, hardeners or catalysts.
- Fast & simple installation process.
- Once opened, the liquid will remain suitable for use if stored correctly - no more wasted liquid!

The substrate should be sound and completely free of any dust, grease, oil, and debris.

Mix the product for 1 minute. This can be done by simply agitating the foil bag, or by pouring into the bucket.

The product can then be poured directly onto the substrate and spread using a roller or brush, adhering to consumption ratios.

The product can be applied to damp substrates. (Any excess or standing water should be wiped away before application.)

The correct consumption ratio is **3KG per square metre**.

Easy-Trim recommends using a reinforcement tape on any joints or seams, or substrate changes i.e. lips, steps, changes in direction etc.

Once opened, the liquid will be suitable for use re-use, if stored correctly in the tub with the lid on.

Large Scale Installations - Easy-Trim Special 1 has been fully tested to obtain W2 (EN Standard) for use without reinforcement. However, for large scale projects or installations where a longer life expectancy is required, a reinforcement can be used, and is recommended.

Contact the Easy-Trim Technical Department for more advice - Technical@easy-trim.co.uk.

COLOUR	Black & Grey
SPECIFIC WEIGHT	1,40 ca g/ml
SKIN FORMATION (20°C 50%UR)	40 minutes
CURING RATE (20°C 50% UR)	2.5mm in 24 hours
ELONGATION AT BREAK	250%
APPLICATION TEMPERATURE	+5°C at + 35°C
OPERATING TEMPERATURE	-30°C at +80°C

Limitations - Please ensure the correct consumption ratios are followed, failure to do so may result a system failure.

If working at lower temperatures, we recommend applying thinner coats to facilitate the curing process. The product can be re-coated if necessary.

For installations where there is standing water, we recommend removing the excess water to avoid the brush or roller sliding out.

Storage - Store the product in its original packaging, in a dry place away from sunlight, at temperatures between +5°C to +25°C. The stability of the product is 12 months from the date of manufacture when stored according to instructions.

Safety - For safety standards, please refer to the safety datasheet.

easy-trim 
Roofing & Construction Products

Tel: 01282 930680 | Email: sales@easy-trim.co.uk | Web: www.easy-trim.co.uk



SPECIAL 1
DATASHEET