



SPECIAL 1

WHATEVER THE WEATHER**PRODUCT:** Special 1**DESCRIPTION:** Special 1 is a single-component liquid membrane that can be applied on wet and dry substrates. Suitable for use on new roofs and existing membranes.**FEATURES & BENEFITS:**

- Can be applied on wet substrates.
- Easy to Install
- Can be used on existing membranes.
- Quick Curing
- Fully UV stable
- Certified for use without reinforcement.
- Odourless & Solvent free
- Isocyanate free
- Excellent adhesion
- Suitable for use on most substrates.
- Resistant to standing water

INSTALLATION GUIDANCE:

- The substrate should be sound and completely free of any dust, grease, oil, and debris.
- Mix the product for 1 minute. This can be done by simply agitating the foil bag, or by pouring into the bucket.
- The product can then be poured directly onto the substrate and spread using a roller or brush, adhering to consumption ratios.
- The product can be applied to damp substrates and is self-levelling.
- The correct consumption ratio is 3KG per square metre.
- Easy-Trim recommends using reinforcement tape on any joints or seams, or substrate changes i.e. lips, steps, changes in direction etc.
- Once opened, the liquid will be suitable for use for re-use, if stored correctly in the tub with the lid on.

LARGE SCALE INSTALLATIONS: Easy-Trim Special 1 has been fully tested to obtain W2 (minimum 10 Year life expectancy) without reinforcement. However, for large scale projects (20 msq or above) or for installations where a longer life span is required, a reinforcement can be used, and is recommended. Contact the Easy-Trim technical department for more information.**LIMITATIONS:** Please ensure the correct consumption ratios are followed, failure to do so may result a system failure. If working at lower temperatures, we recommend applying thinner coats to facilitate the curing process. The product can be recoated if necessary. For installations where there is standing water, we recommend removing the excess water to avoid the brush or roller sliding out.**STORAGE:** Store the product in its original packaging, in a dry place away from sunlight, at temperatures between +5 degrees to +25 degrees C. The stability of the product is 12 months from the date of manufacture when stored according to instructions.**SAFETY:** For safety standards, please refer to the safety datasheet.

PRODUCT DESCRIPTION	PRODUCT CODE		SIZE	BOX QTY	PALLET QTY
	BLACK	GREY			
SPECIAL 1	ET/SP1/15KG	ET/SP1/15KG/GREY	15KG	Singles	38

BASIS	COLOUR	SPECIFIC WEIGHT	SKIN FORMATION	CURING RATE	ELONGATION AT BREAK	APPLICATION TEMP	OPERATIONAL TEMPERATURE	UV RESISTANCE
MS Polymer	Black	1,40 ca g/ml	(20°C 50%UR) 40 minutes	(20°C 50% UR) 2,5MM in 24 hours	250%	+5°C at + 35°C	-40°C at +100°C	Excellent
MS Polymer	Grey	1,40 ca g/ml	(20°C 50%UR) 40 minutes	(20°C 50% UR) 2,5MM in 24 hours	250%	+5°C at + 35°C	-40°C at +100°C	Excellent

Unit 12B, Metcalf Drive,
Altham Industrial Estate,
Altham, Lancashire,
England, BB5 5TU



Tel 01282 930680
sales@easy-trim.co.uk
www.easy-trim.co.uk