



COLOURS

AG Paving Blocks

HomePave

traditional paving blocks with a subtly cobbled surface finish and a smooth finish

DEPTHS



50 | 60
Millimetres

FINISHES

Cob **Smo**
Cobble Smooth

mixed 3 size pack

Mixed pack only **Mixed pack only** **Mixed pack only**
200 x 150mm 150 x 150mm 100 x 150mm

Mixed pack only **Mixed pack only**
200 x 150mm 150 x 150mm

HomePave
colours

COLOURS

For 'Stock Information' on colours availability - see page 3.



AUBURN COBBLE (3 MIXED SIZES)



COVE COBBLE (3 MIXED SIZES)



ASH COBBLE (3 MIXED SIZES)



AUBURN SMOOTH (200x150)



COVE SMOOTH (200x150)



ASH SMOOTH (200x150)



Frost
Resistant



Pedestrian
Use



Light
Traffic



Abrasion
Resistant



Trolley
Friendly
Smooth only



Heavy
Traffic
80mm only



Available in
permeable
(Xflo)

HomePave

traditional paving blocks with a subtly cobbled surface finish and a smooth finish

DEPTHS



50 | 60
Millimetres

FINISHES

Cob **Smo**
Cobble Smooth

mixed 3 size pack

Mixed pack only **Mixed pack only** **Mixed pack only**
200 x 150 x 150mm 150 x 150 x 150mm 100 x 150 x 150mm

200 x 150 x 150mm 150 x 150 x 150mm

STANDARDS + PERFORMANCE



Product Type	Traditional paving blocks with a subtly cobbled surface finish and a smooth finish
Manufactured to	hEN 1338:2003
Surface Layer	Durable and hard wearing with a minimum surface layer of 8mm.
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Tensile Splitting Strength	>3.6Mpa. This applies to all sizes and depths. For specific force performance on a given size or depth please contact our Technical Specification Department. HomePave 50mm is suitable for driveways with cars, caravans, vans, motorhomes, etc.
Installed to	BS 7533-4:2006
NBS Plus	Q24 110

SUSTAINABILITY

BES 6001	Responsible Sourcing of Concrete Products (Rating: Very Good)
Energy Use	100% renewable
Water Used	90% recycled water
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK using responsibly sourced materials
Non-Primary Materials	52 – 60%
Waste Wood + Plastic	100% recycled
BREEAM	50 – 60mm: A Rating – according to the Green Guide to Specification 4th edition 2009. A+ Rating can be achieved when used in conjunction with a prepared recycled sub-base
	80mm: B Rating – according to the Green Guide to Specification 4th edition 2009. A Rating can be achieved when used in conjunction with a prepared recycled sub-base.


EDGES

HomePave 3's Supplied with a subtly cobbled edge.





Cobbled Edge
(No Chamfer)

HomePave Supplied with either a subtly cobbled edge or a smooth edge.



Xflo HomePave Supplied with either a subtly cobbled edge or a smooth edge.



SPACER NIBS

HomePave 50mm 1.5mm as standard.

Xflo HomePave 60mm / 80mm
Supplied with 'invisible' 3.25mm x 10 spacers nibs on each paver leaving a 7mm minimum joint. The nibs are dropped, so they are invisible on the finished surface.

HIGH SPEED FLOW RATE

Xflo Supports a flow rate of 4000mm/hr/m².

FINISHES

HomePave is made with colourfast UV resistant materials for vibrant, durable and lasting colours. HomePave Cobble has a subtly cobbled finish made using new state-of-the-art manufacturing facilities. HomePave Smooth is an as-cast finish with square edges.



Frost Resistant



Pedestrian Use



Light Traffic



Abrasion Resistant



Trolley Friendly
Smooth only



Heavy Traffic
80mm only



Available in permeable
(Xflo)

SPECIFICATION REFERENCE: NBS PLUS: Q24 110 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315; hEN: 1338:2003



HomePave

traditional paving blocks with a subtly cobbled surface finish and a smooth finish

DEPTHS



50 | 60
Millimetres

FINISHES



Cobble



Smooth

mixed 3 size pack



200 x
150mm



150 x
150mm



100 x
150mm



200 x
150mm



150 x
150mm

AG RECOMMENDATIONS

Close Jointing

AG recommends a close joint of between 2mm - 5mm as per BS 7533 to cater for product alignment (products should never be butt jointed).

Jointing Sand

AG recommends that silver and slate coloured products are jointed with AG's Silver Granite Sand.

Colour blending

AG recommends that products are blended from 3 packs from alternate sides using full vertical sections.

Please contact our Technical Specification Department for further details.

ADVICE + GUIDANCE

For advice and guidance on ordering, installation, good site practice, etc. visit our website:
www.ag.uk.com/advice+guidance

For maintenance guidance and health and safety advice visit our website:
www.ag.uk.com/maintenance



Frost
Resistant



Pedestrian
Use



Light
Traffic



Abrasion
Resistant



Trolley
Friendly
Smooth' only



Heavy
Traffic
80mm only



Available in
permeable
(Xflo)

ENVIRONMENTAL PRODUCT DECLARATION (EPD)

An EPD is a comprehensive document that quantifies the environmental impact of a product or range over its entire life cycle.

At AG we exist to develop and create the most sustainable paving and building products available today.

Read more about AG's commitment to sustainability [here](#), download our Corporate Social Responsibility (CSR) brochure [here](#) and download our latest EPDs [here](#).

Product Depth	GWP Total A1-A3 kgCO2e per m2	GWP Total A1-A3 kgCO2e per m3
50mm	8.40	168
60mm	10.08	
80mm	13.44	

HomePave

traditional paving blocks with a subtly cobbled surface finish and a smooth finish

DEPTHS



50 | 60
Millimetres

FINISHES












Cob **Smo**
Cobble Smooth

mixed 3 size pack

Mixed pack only **Mixed pack only** **Mixed pack only**
200 x 150mm 150 x 150mm 100 x 150mm

200 x 150mm 150 x 150mm

STOCK INFORMATION

Standard product depth	Size (mm)	In Stock	Available Colours	m² per pack	Units per layer	Total units per pack	Units per pack	Unit weight (kg)	Weight per pack (t)	Packs per 8 wheeler (Ireland)	Packs per unit lorry (GB/Ireland)
50mm	 200 x 150	Yes	Auburn Cobble / Auburn Smooth / Cove Cobble / Cove Smooth / Ash Cobble / Ash Smooth	12.96	36	432	—	3.45	1.49	9	IRE 13 / GB 18
HomePave 3s Cobble new sizes — Mixed Size Pack (paving blocks not sold individually)											
50mm  (mixed pack only)	<small>mixed 3 size pack</small>  200 x 150	Yes	Auburn Cobble / Cove Cobble / Ash Cobble	12.96	16	576	192	3.45	1.49		IRE 13 / GB 18
	 150 x 150				16		192	2.59			
	 100 x 150				16		192	1.73			
Xflo HomePave 3's Cobble new sizes — Mixed Size Pack (paving blocks not sold individually)											
60mm 	<small>mixed 3 size pack</small>  200 x 150	Yes	Natural Grey Cobble / Cove Cobble / Ash Cobble	12.96	—	576 192 of each size	—		1.728	9	15
	 150 x 150	—	—								
	 100 x 150	MTO	Burren Cobble		—						
Xflo HomePave 3's Smooth new sizes — Mixed Size Pack (paving blocks not sold individually)											
60mm 	<small>mixed 3 size pack</small>  200 x 150	Yes	Natural Grey Smooth / Cove Smooth / Ash Smooth	12.96	—	576 192 of each size	—		1.728	9	15
	 150 x 150	—	—								
	 100 x 150	MTO	Burren Smooth		—						

MTO: Made To Order (minimum order quantities: 250m² per colour / size. Orders below these quantities should be priced on application).

Information for a specific colour / depth is available on request from our Technical Specification Department.

The Mixed Size pack is supplied in a mix of three different sized units (unit sizes are not sold individually).

There are 12 layers in the Xflo 3's Mixed Size pack (1.08m² per Layer).

An easy-to-follow laying pattern is included for the Mixed Size range.

HomePave 50mm is suitable for driveways with cars, caravans, vans, motorhomes, etc.

Information for a specific colour / depth is available on request from our Technical Specification Department.



Frost Resistant



Pedestrian Use



Light Traffic



Abrasion Resistant



Trolley Friendly
Smooth' only



Heavy Traffic
80mm only



Available in permeable (Xflo)

MANUFACTURING

HomePave is manufactured from high grade locally sourced aggregates. Its colour blends are obtained by using the latest computerised mixing systems. HomePave Cobble has a subtly cobbled finish made using new state-of-the-art manufacturing facilities. HomePave Smooth is an as-cast finish with square edges.
PLANT OF MANUFACTURE: Made at our Toome production plant.

CERTIFICATION

BES 6001
ISO 9001
ISO 14001
ISO 45001
CE Marking

Responsible Sourcing of Concrete Products (Rating: Very Good)
Quality Management.
Environmental Management.
Occupational Health and Safety Management.
Download our Declaration of Performance (DOP) data at:
www.ag.uk.com/resources