

Luminaires | Fire Rated Downlights

R6™CS Fixed 6W Colour Switchable Fire Rated Downlight with FastRFix

AU-R6CSFF



Photometrics

Wattage	6
Lumens	540 - 620
Lm/W	103
Beam Angle	60
Colour Temperature	3000 / 4000 / 5700
Ra	80
SDCM	6

Product Features

Brand	Aurora
IP Rating	IP65
L70 Hours	L70 40,000
Lifetime Class	L70
Dimmable	Yes
0-10V Dimming?	No
DALI Dimming?	No
1-10V Dimming?	No
DALI-2 Dimming?	No

DMX Dimming?	No
DSI Dimming?	No
Warranty	5 Years

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.85
Surge Protection (kV)	1.5
Protection Class	Class 2
Frequency (Min) Hz.	50
Frequency (Max) Hz.	50
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	45

Physical Attributes

Height (mm)	50
Overall Diameter (mm)	88
Cutout Diameter Min. (mm)	65
Cutout Diameter Max. (mm)	70
Product Weight (KG)	0.225
Gross Weight - Product & Box (KG)	0.279
Material	Polycarbonate & Pressed Steel
Optic Material	Clear Multifaceted
Diffuser	Clear
Mount Options	Recessed
Packaging Length (mm)	100
Packaging Width (mm)	100
Packaging Height (mm)	95
Outer Packaging Length (Inches)	3.93
Outer Packaging Width (Inches)	8.84

Outer Packaging Height (Inches)

8.25

Barcode

5056100000000