

fermacell™ Screws

For wall and ceiling construction with fermacell® gypsum fibreboards

For fixing fermacell® gypsum fibreboard to metal or timber studs and joists.

Application

The screws can be used for single and multi-layer fixing of fermacell® boards into timber or metal studwork and joists. fermacell™ Drill tip screws (3·5 × 30 mm) can be used on metal studwork up to 2 mm in gauge. fermacell™ screws can be fixed close to the edge of the boards (approx. 10 mm) without splitting. fermacell™ screws can be screwed directly into the board so no pre-drilling is required.

Screws can be fixed with electric screwdrivers (approx. 500 W, with a speed 0-4000 rpm) or with most leading brands of screw guns using compatible drill bits.

Properties

fermacell™ screws are characterised by the following properties:

- **Easy to screw in**
 - The optimised thread geometry provides fast penetration and guarantees a perfect perfect hold in the sub-frame
 - Use a Phillips PH2 bit for installing the screws
- **Self countersinking**
 - The geometry of the head enables perfect countersinking of the screw into the boards
- **Rustproof**
 - Galvanized with a zinc phosphate coating to DIN 50942
- **Suitable for use with most electric screwdrivers**
 - The fermacell™ collated screws can be installed with most brands of screw guns, eg, Hilti, Makita, Hitachi and Senco.

Spacing and material specification

Refer to tables starting on page 2.

Types of screws					
Sizes (mm)	3·9 × 30	3·9 × 30 Collated	3·9 × 30 Drill Tip	3·9 × 40	3·5 × 55
Quantity per box	1000 / 250	1000 (50x20)	1000 / 250	1000	1000
Part no: 4007548..	79011/ 79021	79049	79052/ 79048	79047	79053
EAN 4007548..	..001601 ..001663	..014007	..014045 ..014038	..014021	..014014
Duty no:	73181290	73181290	73181290	73181290	73181290
Weight per pack	2·1 kg 0·65 kg	2·6 kg	2·1kg/ 0·65kg	2·6 kg	3·4 kg
Pack/Cartron	10/40	10	10/40 ext	10	10
Weight/ Carton	~ 21 kg ~ 26 kg	~ 26 kg	~ 21 kg ~ 26 kg	~ 26 kg	~ 34 kg



Fermacell UK,
Division of James Hardie Building
Products Ltd
7 The Priory
Old London Rd
Sutton Coldfield B75 5SH

Technical support

Tel 0121 311 3480
E-mail info@jameshardie.co.uk
Web www.fermacell.co.uk



Type, spacings and usage of fixing single and multi-layers of fermacell® board back to steel or timber stud. For non-load bearing partitions.

Walls			
Board thickness /Construction	fermacell™ Screws		
Metal stud - 1 layer	Length (mm)	Spacing (mm)	Usage [No/m²]
10 mm	30	250	26
12.5 mm	30	250	20
15 mm	30	250	20
18 mm	40	250	20
Metal stud – 2-layers. 2nd layer fixed into the stud			
1st layer 10 mm	30	400	16
2nd layer 10 mm	40	250	26
1st layer 12.5 mm or 15 mm	30	400	12
2nd layer 10 mm, 12.5 mm or 15 mm	40	250	20
Metal stud – 3-layers, 1 to 3 layers fixed into the stud			
1st layer 12.5 mm or 15 mm	30	400	12
2nd layer 10 mm or 12.5 mm	40	400	12
3rd layer 10 mm or 12.5 mm	55	250	20
Timber stud – 1 layer			
10 mm	30	250	26
12.5 mm	30	250	20
15 mm	30	250	20
18 mm	40	250	20
Timber stud - 2 layers, 2nd layer fixed into the stud			
1st layer 10 mm	30	400	16
2nd layer 10 mm	40	250	26
1st layer 12.5 mm	30	400	12
2nd layer 12.5 mm	40	250	20
1st layer 15 mm	40	400	12
2nd layer 12.5 mm or 15 mm	40	250	20
Timber stud - 3 layers, 1 to 3 Layers fixed into the stud			
1st layer 12.5 mm	30	400	12
2nd Layer 10 mm or 12.5 mm	40	400	12
3rd layer 10 mm or 12.5 mm	55	250	20

We reserve the right to change specifications. Version 10/2019
Please ensure that you are in possession of the current version.
If you need technical assistance then please call our helpline.

Type, spacing and usage of fixing fermacell® board to board.

Walls – fixing board to board			
Board thickness/construction	fermacell™ Screws Screw rows ≤ 40 cm		
Wall division per m² wall area	Length (mm)	Spacing (mm)	Usage (No/m²)
10 on 10 or 12.5	30	250	26
12.5 on 12.5 or 15	30	250	26
15 on 15	30	250	26
18 on 18	40	250	26

- In multiple layer wall constructions with 10 mm fermacell® gypsum fibreboards, the last layer of board can be fastened with 55 mm fermacell™ screws directly into the sub-frame.
- In walls with fire protection criteria, fastening intervals differing from this table may be mandated by the relevant test certificates.
- 30 mm fermacell™ Drill tip screws can be used to secure 10 mm, 12.5 mm or 15 mm fermacell® boards to steel stud work with a gauge of up to 2 mm. You should use approx. 4 screws per metre run of board.

We reserve the right to change specifications. Version 10/2019
Please ensure that you are in possession of the current version.
If you need technical assistance then please call our helpline.

Spacing and use of fixings in ceilings per m² of ceiling area.

Ceilings			
Board thickness /Construction	fermacell™ Screws		
Metal - 1 layer	Length [mm]	Spacing [mm]	Usage [No/m ²]
10 mm	30	200	22
12.5 mm	30	200	19
15 mm	30	200	16
Metal – 2-layers, 2nd layer fixed into sub-frame			
1st layer 10 mm	30	300	16
2nd layer 10 mm	40	200	22
1st layer 12.5 mm	30	300	14
2nd Layer 12.5 mm	40	200	19
1st Layer 15 mm	30	300	12
2nd Layer 12.5 mm or 15 mm	40	250	16
Metal – 3-layers, 1 to 3 layers fixed into sub-frame			
1st Layer 15 mm	30	300	12
2nd Layer 12.5 mm	40	300	12
3rd Layer 12.5 mm	55	200	16
Timber – 1-layer			
10 mm	30	200	22
12.5 mm	30	200	19
15 mm	40	200	16
Timber – 2-layers, 2nd layer fixed into the sub-frame			
1st layer 10 mm	30	300	16
2nd layer 10 mm	40	200	22
1st layer 12.5 mm	30	300	14
2nd layer 12.5 mm	40	200	19
1st layer 15 mm	40	300	12
2nd layer 12.5 mm or 15 mm	40	200	16
Timber stud - 3 layers, 1 to 3 Layers fixed into the stud			
1st Layer 15 mm	40	300	12
2nd Layer 12.5 mm	40	300	12
3rd Layer 12.5 mm	55	200	16

We reserve the right to change specifications. Version 10/2019
Please ensure that you are in possession of the current version.
If you need technical assistance then please call our helpline.

Type, spacing and usage of fixing fermacell® board to board.

Ceilings - fixing board to board			
Board thickness/construction	fermacell™ Screws Screw rows ≤ 30 cm		
Ceiling spacing per m² ceiling	Length (mm)	Spacing (mm)	Usage [No/m²]
10 mm to 10 mm or 12.5 mm	30	150	30
12.5 mm to 12.5 mm or 15 mm	30	150	30
15 mm to 15 mm	30	150	30

Note:

- In multiple layer ceiling constructions with 10 mm fermacell® gypsum fibreboard, the last layer of board can be fixed with fermacell™ 55 mm screws directly into the sub-frame.
- In ceilings with fire protection criteria, fastening intervals differing from this table may be mandated by the relevant test certificates.
- fermacell™ 30 mm drill tip screws can be used to secure 10 mm, 12.5 mm or 15 mm
For fixing fermacell® gypsum fibreboards to steel sub frames of up to 2 mm thickness, the usage should be approx.
5 screws per m².

We reserve the right to change specifications. Version 09/2019 Please ensure that you are in possession of the current version. If you need technical assistance then please call our helpline.