Silicone Neutral Transparent

Version	Revision Date:	SDS Number:	Date of last issue: 09.08.2024
8.0	22.08.2024	9171343-00014	Date of first issue: 29.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Silicone Neutral Transparent

Product code : 089285431

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Sealant
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Wurth UK Ltd
1 Centurion Way
Erith, Kent

Telephone : +44 (0)3300 555 444

Telefax : +44 (0)3300 555 666

E-mail address of person responsible for the SDS : prodsafe@wuerth.com

1.4 Emergency telephone number

+44 (0)870 190 6777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

EUH210 Safety data sheet available on request.

EUH208 Contains 3-Aminopropyltriethoxysilane. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics	64742-46-7 01-2119552497-29	Asp. Tox. 1; H304	>= 1 - < 10
Silsesquioxanes, 3-aminopropyl Me, ethoxy-terminated	128446-60-6	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 1 - < 10
3-Aminopropyltriethoxysilane	919-30-2 213-048-4 612-108-00-0	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 0.1 - < 1
Substances with a workplace exposure limit :			
Silicon, amorphous	112945-52-5		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact	:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks	:	May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	:	Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Carbon oxides Silicon oxides Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
If spillage enters rivers or watercourses, inform the Environment Agency (emergency telephone number 0800 807060).

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing vapours.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure assessment
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Gases

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silicon, amorphous	112945-52-5	TWA (inhalable dust)	6 mg/m3 (Silica)	GB EH40
		TWA (Respirable dust)	2.4 mg/m3 (Silica)	GB EH40

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m3	GB EH40
Methanol	67-56-1	TWA	200 ppm 266 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	250 ppm 333 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned sub-			

	stances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	200 ppm 260 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			

Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
3-Aminopropyltriethoxysilane	Workers	Inhalation	Long-term systemic effects	14 mg/m3
	Workers	Skin contact	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3.5 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1 mg/kg bw/day
Triethoxy(vinyl)silane	Workers	Inhalation	Long-term systemic effects	71.08 mg/m3
	Workers	Skin contact	Long-term systemic effects	10.26 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	17.37 mg/m3
	Consumers	Skin contact	Long-term systemic effects	5.036 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	5.036 mg/kg bw/day

Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
Triethoxy(vinyl)silane	Fresh water	0.56 mg/l
	Marine water	0.056 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	2.06 mg/kg
	Marine sediment	0.206 mg/kg
	Soil	0.085 mg/kg
3-Aminopropyltriethoxysilane	Fresh water	0.5 mg/l
	Freshwater - intermittent	2.05 mg/l
	Marine water	0.05 mg/l
	Sewage treatment plant	0.81 mg/l
	Fresh water sediment	1.8 mg/kg dry weight (d.w.)
	Marine sediment	0.18 mg/kg dry weight (d.w.)
	Soil	0.069 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection	:	Wear the following personal protective equipment: Safety glasses Equipment should conform to BS EN 166
Hand protection		
Material	:	butyl-rubber
Break through time	:	> 480 min
Glove thickness	:	> 0.3 mm
Material	:	Nitrile rubber
Break through time	:	30 - 60 min
Glove thickness	:	> 0.2 mm
Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Skin and body protection	:	Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	:	If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to BS EN 137
Filter type	:	Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	paste
Colour	:	coloured
Odour	:	characteristic
Odour Threshold	:	No data available

pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	> 250 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	1.02 g/cm³ (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	> 400 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids)	:	Ignitable (see flash point)
Particle size	:	Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon contact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
Water

10.6 Hazardous decomposition products

Contact with water or humid air : Ethanol
Methanol

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.266 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 3,160 mg/kg

3-Aminopropyltriethoxysilane:

Acute oral toxicity : LD50 (Mouse): 530 mg/kg

Acute inhalation toxicity	:	LC50 (Rat): > 4.41 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Acute dermal toxicity	:	LD50 (Rabbit, male): 3,772 mg/kg

Silicon, amorphous:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 2.08 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Silsesquioxanes, 3-aminopropyl Me, ethoxy-terminated:

Result	:	Skin irritation

3-Aminopropyltriethoxysilane:

Species	:	Rabbit
Result	:	Corrosive after 3 minutes to 1 hour of exposure

Silicon, amorphous:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

Silsesquioxanes, 3-aminopropyl Me, ethoxy-terminated:

Result	:	Irritation to eyes, reversing within 21 days

3-Aminopropyltriethoxysilane:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

Silicon, amorphous:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

3-Aminopropyltriethoxysilane:

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	positive
Assessment	:	Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

3-Aminopropyltriethoxysilane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Silicon, amorphous:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Carcinogenicity - Assessment : Classified based on the conditions cited in Nota N (Regulation (EC) 1272/2008, Annex VI, Part 3, Note N)

3-Aminopropyltriethoxysilane:

Species : Mouse
Application Route : Skin contact

Exposure time : 24 Months
Result : negative

Silicon, amorphous:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Silicon, amorphous:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

3-Aminopropyltriethoxysilane:

Species : Rat
NOAEL : 200 mg/kg
LOAEL : 600 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Silicon, amorphous:

Species : Rat

NOAEL	:	1.3 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Toxicity to fish	:	LL50 (Scophthalmus maximus (turbot)): > 1,028 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Acartia tonsa (Calanoid copepod)): > 3,193 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: ISO 14669 and PARCOM method
Toxicity to algae/aquatic plants	:	EL50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: ISO 10253
Toxicity to microorganisms	:	EC50 : > 100 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

3-Aminopropyltriethoxysilane:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 934 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 331 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic	:	EL50 (Skeletonema costatum (marine diatom)): 863 mg/l

plants

Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: ISO 10253

NOELR (Skeletonema costatum (marine diatom)): 40 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: ISO 10253

Toxicity to microorganisms : EC10 (Pseudomonas putida): 13 mg/l
Exposure time: 5.75 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: Based on data from similar materials

Silicon, amorphous:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0,03% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 74 %
Exposure time: 28 d
Method: OECD Test Guideline 306

3-Aminopropyltriethoxysilane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 67 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.A.

12.3 Bioaccumulative potential

Components:

3-Aminopropyltriethoxysilane:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 3.4
Method: OECD Test Guideline 305C

Partition coefficient: n-octanol/water : log Pow: -1.3
Remarks: Calculation

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

Waste Code	:	The following Waste Codes are only suggestions: used product 08 04 10, waste adhesives and sealants other than those mentioned in 08 04 09 unused product 08 04 10, waste adhesives and sealants other than those mentioned in 08 04 09 uncleaned packagings 15 01 06, mixed packaging

SECTION 14: Transport information

14.1 UN number

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.2 UN proper shipping name

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.4 Packing group

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation	:	Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH)
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 0.1 %

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information	:	Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
2006/15/EC	:	Europe. Indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2006/15/EC / TWA	:	Limit Value - eight hours
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN