

Product Code: CMA036

## **Technical Specification**

Luckinslive 389086884



Description: 13A 2 Gang Double Pole Switched Socket Outlet



Rear Housing: Urea

Terminal Torque Value (Nm) 2

Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

## **General Information**

Plate Dimensions (mm) 146 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Style Rounded Profile Colour Polar White

> > Yes

Materials Front Plate & Rocker Switch: Urea

Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

Earth Strap: Mild Steel

Anti Microbial Certified Frequency (Hz) 50

Operating Voltage (AC) 250 Resistive Load Rating (A) Termination Type Screw

Terminal Size (mm) Ø5 Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Twin Earth Terminals Minimum Back Box Depth (mm) IP20 Ingress Protection Operational Temperature (°C) -5 to +40

Warranty (Years)

Standards BS 1363-2


## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Specification is subject to change without notice. Errors & Omissions excluded.











Scolmore House, Mariner, Lichfield Road Industrial Estate,