



Product Code: PRC00g  
Description: 10AX 2 Way Pull Cord Switch

Luckinslive 38g120232



General Information

Dimensions (mm)	76 (Dia) x 51.5		
Style	Round		
Colour	Polar White		
Materials	Cover & Pattress: Urea	Terminal Housing: Urea	
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated	
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel	
	Pull Bell: Urea		
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Inductive Load Rating (AX)	10		
Load Rating Comments	Suitable for Fluorescent or Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm)	0.4
Terminal Capacity - Solid (mm²)	2 x 1.5 or 1 x 2.5		
2 Way Switch	Yes		
Twin Earth Terminals	No		
Supplied Back Box Depth (mm)	Pattress Supplied		
Back Box Knockouts - Total (mm)	4 x 12 x 9 and 1 x 17 x 23		
Back Box Knockouts - Top (mm)	None	Back Box Knockouts - Sides (mm)	4 x 12 x 9
Back Box Knockouts - Bottom (mm)	None	Back Box Knockouts - Rear (mm)	1 x 17 x 23
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.  
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Catalogue



Range



DoC



Installation

