



General Information

Dimensions (mm)	76 (Dia) x 51.5	
Style	Round	
Colour	Polar White	
Materials	Cover & Pattress: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass Pull Bell: Urea	Terminal Housing: Urea Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel
Anti Microbial Certified	Yes	
Operating Voltage (AC)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø4	Terminal Torque Value (Nm) 0.4
Terminal Capacity - Solid (mm²)	2 x 1.5 or 1 x 2.5	
2 Way Switch	Yes	
Twin Earth Terminals	No	
Supplied Back Box Depth (mm)	Pattress Supplied	
Back Box Knockouts - Total (mm)	4 x 12 x 9 and 1 x 17 x 23	
Back Box Knockouts - Top (mm)	None	Back Box Knockouts - Bottom (mm) None
Back Box Knockouts - Rear (mm)	1 x 17 x 23	Back Box Knockouts - Sides (mm) 4 x 12 x 9
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards

BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.