

Ventilation Fans



Description

A range of slim and stylish ventilation fans suitable for bathrooms, toilets and kitchens.

Features

- Sleek design
- Low energy fans – meet Building Regulation L1A specific fan power of less than 0.5W/l/s
- Low noise fans – meet Building Regulation F1 by being under 35dB for less noise sensitive rooms
- Over run timers factory set at 15 minutes
- Humidistat factory set at 75% RH
- Ideal for through wall applications or with ducting lengths under 2m
- Fans have a one shot thermal fuse
- 3-year guarantee

Range

4" (100mm) Standard	4600
4" (100mm) Timer	4601
4" (100mm) Timer & Humidistat	4603
6" (150mm) Standard	4660
6" (150mm) Timer	4661
4" (100mm) Flat Fascia Standard	4630
4" (100mm) Flat Fascia Timer	4631
6" (150mm) Humidistat & Auto Shutters	4666

Technical Specification

	4"	4" Flat Fascia	6"	6" Humidistat & Auto Shutters
Extraction rate	25 l/s (90m ³ /hr)	26 l/s (92m ³ /hr)	71 l/s (255m ³ /hr)	71 l/s (255m ³ /hr)
Specific Fan Power	0.32W (l/s)	0.49W (l/s)	0.40W (l/s)	0.40W (l/s)
Noise level	29dB @ 3m	34dB @ 3m	35dB @ 3m	35dB @ 3m
Voltage	240Vac	240Vac	240Vac	240Vac
Motor Rating	8W	13W	28W	28W
IP Rating	IP 24	IP 24	IP 24	IP 24
Ambient Temp	40°C Max.	40°C Max.	40°C Max.	40°C Max.
Insulation Class	Double Insulated	Double Insulated	Double Insulated	Double Insulated
Over Run Timer	2-30mins.	2-30mins.	2-30mins.	2-30mins.
Humidistat	60-90% RH			60-90% RH
Dimensions	150 x 150 x 19	205 x 205 x 51	205 x 205 x 22	205 x 205 x 22

No user serviceable parts

Standards

- BS EN 60335-2-80