



Additional Information

Prevents cross contamination

Chrome finish single check valve

DZR brass pressure reducing valve

CPR compliant safety relief valve

Wide variety of kits available

Protects water heaters from excess pressure from the main

Expansion vessel absorbs increased water volume as it's heated


WRAS approved 2 ltr expansion vessel

Product


Unvented Water Heater Accessory Packs

Code	Description
INAQ2	2 Ltr Potable Vessel and Single Check Valve
INAQ3	1/2" Pressure Reducing Valve
INAQ4	2 Ltr Potable Vessel, Single Check Valve, PRV & SRV
INAQ5	2 Ltr Potable Vessel, Single Check Valve and SRV
INAQ6	2 Ltr Potable Vessel, Single Check Valve and PRV Incl Gauge
INAQ7	2 Ltr Potable Vessel, Single Check Valve, PRV Incl Gauge, Swivel SRV
INAQ8	2 Ltr Potable Vessel, Single Check Valve, and Swivel Nut SRV


Technical Specification




Maximum inlet pressure (static)	16 Bar
Maximum inlet temperature	80°C
Factory pre-set outlet pressure	3 Bar
Adjustable pressure range	0.5 - 6 Bar
Minimum working pressure	0.5 Bar



Maximum operating pressure	10 Bar
Maximum operating temperature	70°C
Factory pre-charge pressure	3.5 Bar
Membrane	Butyl



Factory set discharge pressure	6 Bar
Maximum operating pressure (static)	10 Bar
Maximum working temperature	110°C



Minimum working pressure	0.2 Bar
Maximum working pressure (static)	10 Bar
Maximum working temperature	70°C

Typical Installation

