# **Technical data sheet**

#### FB20

#### **Fixing Band**



FB20 fixing band is for all general light strapping needs.

Perfect for DIY, industrial and agricultural applications. Comes in convenient 10 metre rolls. FB20 comes supplied in a rugged plastic dispenser, making it much easier to transport and work with.

### **Features**

#### Material

• Galvanized steel S250GD + Z275 according to BS EN 10346.

## **Applications**

#### **Features**

- Supplied on a 10 metre roll.
- Suitable for internal applications only
- Strap is punched with two different sized round holes and 1 square hole, to enable a variety of different fixings to be used
  - Nails
  - Screws
  - Coach Screws





# **Technical data sheet**

FB20

### **Fixing Band**



## **Technical Data**



#### Product Dimensions

References	Dimensions			Holes [mm]			Strap Minimum Section [mm2]	Pkg.
	Α	В	t	Size (Round)	Size (Round)	Size (Square)	ouap wiimindin occuon [min2]	i ng.
FB20	20	10 m	0.9	Ø4	Ø7	7x7	10.8	10

<sup>\*</sup> Not covered by CE certification





### Characteristic Capacities

References	Strap Characteristic Tensile Capacity [kN]		
Neierences	R <sub>1,k</sub>		
FB20	3		

#### Note:

- The capacity of the connection is the lower of the straps declared characteristic tensile capacity or the fixing capacity.
- The quanity, type and size of fixings along with its spacings, edge distances and fixing substrates should be considered when determining the capacity of the connection.

# **Technical data sheet**

FB20

### **Fixing Band**



## Installation

### Fixings

- Nails
- Screws
- · Coach Screws

**Fixing Band** 

2025-01-30

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG tel: +44 1827 255600 fax: +44 1827 255616 Copyright by Simpson Strong-Tie® Information presented on this document is the exclusive property of Simpson Strong-Tie® It is valid only when associated with products supplied by Simpson Strong-Tie®



