



EXTERIOR PREGRIT

Extra Grip Render Bonding Agent

Technical Data Sheet



BUILDERS COMPLETE RANGE

Description:

A one part, ready-to-use, extra grip, external render bonding agent with added aggregate to provide a key prior to applying render to exterior substrates.

Features & Benefits:

- ◆ **Bonding agent for exterior walls.**
- ◆ **For use on concrete, brickwork, light blockwork.**
- ◆ **Single application, render once cured.**
- ◆ **Light green in colour for easy identification of treated areas.**
- ◆ **Reduces suction on porous surfaces.**
- ◆ **Improves adhesion on smooth surfaces.**
- ◆ **Waterproof.**
- ◆ **Phthalate free formulation.**

Uses

EXTERIOR PREGRIT is for use as an effective bonding agent for render to concrete, brickwork and blockwork. And as a bonding agent to improve adhesion to smooth surfaces.

Limitations

- Do not use on areas subject to continual damp.
- Do not dilute.
- Do not exceed a maximum thickness of 25mm for complete render system.
- Remove any contamination of product to surrounding surfaces before drying.

Preparation

Thoroughly stir before use. Ensure application temperature is above +5°C and that the surface to be treated is free from dust, release agents and any contaminants that may hinder adhesion. Any contamination must be removed prior to application, including any flaking material. Ensure the background is sound and will support the weight of the render.

Application

Do not dilute. We recommend a patch test be carried out on a small inconspicuous area to test compatibility prior to full application. Simply apply 1 coat using a brush or roller ensuring an even coat and allow to dry (6 hours minimum). This product is coloured light green to identify treated areas. Protect adjacent surfaces from splashes and remove any EXTERIOR PREGRIT before drying using warm soapy water. Note: Cold or humid conditions will increase drying times. Do not use at temperatures below +5°C.

Cleaning Of Tools

Tools can be cleaned with warm soapy water after use.

Size

10L recycled plastic tubs.

Coverage

Depending on porosity of substrate approximately 3m²/L (10L tub will cover approximately 30m²).

Colour

Pale green paste.

Shelf Life

24 months from date of manufacture when stored in unopened tubs.

Storage Conditions

Store in cool, dry conditions in the original sealed container away from direct sunlight. Store between +5°C and +30°C. Protect from frost.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any containers to a central disposal point in accordance with local regulations. Any spillages should be mopped up immediately with an inert absorbent material such as sand or sawdust.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Appearance	Pale green liquid
Composition	Waterbased polymers
Application Temperature	+5°C to +30°C
Density	1.25g/cm³
Viscosity	6,000 - 12,000 cP
Tub PCR Content	30%
Commodity Code	4002910000

Product / Order Details

Code	Colour	Fill	Barcode	UFI
BDEPG10	Pale Green	10L	5060021369710	-



Part of the Bond It Builders Complete Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 2: 23/07/24
Supersedes: V1 06/02/14

bond it

An **ASTRAL** Limited Company