

ProSolve[™] Bitumen Cold Joint Sealer (750ml)

Safety Data Sheet

According to Regulation (EU) No 830/2015 and Regulation (EC) No 1272/2008 Date Revised: 12/10/2020 / Version: 2

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Trade Name: ProSolve Bitumen Cold Joint Sealer Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: Used for roads, potholes etc

1.3. Details of the supplier of the safety data sheet

Company Name: ProSolve

Company Address: Sandall Stones Road, Kirk Sandall Industrial Estate, Doncaster, South Yorkshire, DN3 1QR

Tel: +44 (0) 1302 310 113

E-mail: enquiries@prosolveproducts.com

Web: www.prosolveproducts.com

EU Details:

Address: PO Box: 107, 3150 AC, HOEK VAN HOLLAND

1.4. Emergency Telephone Number

National Health Service (NHS)

NHS England or Scotland: 111

NHS Wales: 0300 0604400

Northern Ireland: Call your local GP

For life-threatening emergencies: call 999 for an ambulance.

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Aerosol 1 Aerosol - Category 1

2.2. Label elements Hazard pictograms:

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word : DANGER

Hazard pictograms



Hazard statements

H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash ... thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P203 Obtain, read and follow all safety instructions before use.

Response

P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	In case of leakage, eliminate all ignition sources.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P363	Wash contaminated clothing before reuse.

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P316	Get emergency medical help immediately.
P321	Specific treatment (see on this label).
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
P305+P354+P338	IF IN EYES: Immediately rinse with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
P317	Get medical help.
P318	IF exposed or concerned, get medical advice
Storage	
P403	Store in a well-ventilated place.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P405	Store locked up.
Disposal	
P501	Dispose of contents/container to an appropriate treatment and disposal facility in
	accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3. Other hazards Results of PBT and vPvB assessment:

No data available

SECTION 3: Composition / Information On Ingredients

Description

A mixture of zinc, additives, solvents and gases.

3.1. Substances N/A

3.2. Mixtures Description: Hazardous Ingredients

Chemical Name	Common name	CAS Number	EC Number	Concentration
Asphalt	Bitumen	8052-42-4	232-490-9	35%

Dimethyl ether	Dimethyl Ether	115-10-6	204-065-8	22%
Talc (Mg3H2(SiO3)4)	Talc Powder	14807-96-6	238-877-9	12%
Petroleum resins	Petroleum Resin	64742-16-1	265-116-8	7%
poly(chloroprene) macromolecule	Chloroprene	9010-98-4	618-463-8	9%
Solvent naphtha (petroleum), heavy arom.	Solvent Naphtha	64742-94-5	265-198-5	10%
none	Mesitylene	2768-92-5	none	5%

SECTION 4: First Aid Measures

4.1. Description of first aid measures

General information:

Medical attention is required. Consult a doctor. Show this safety data sheet (SDS) to the doctor in attendance.

Inhalation:

Move the victim into fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration and consult a doctor immediately. Do not use mouth to mouth resuscitation if the victim ingested or inhaled the chemical.

Skin Problem:

Take off contaminated clothing immediately. Wash off with soap and plenty of water. Consult a doctor.

Eye:

Rinse with pure water for at least 15 minutes. Consult a doctor.

Ingestion:

Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Centre immediately.

4.2. Most important symptoms and effects, both acute and delayed: No data available.

4.3. Indication of any immediate medical attention and special treatment needed: No information available.

SECTION 5: Firefighting Measures

5.1. Extinguishing media

Suitable: Use dry chemical, carbon dioxide or alcohol-resistant foam.

5.2. Special hazards arising from the substance or mixture: no data available

5.3. Advice for fire-fighters: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:

Avoid dust formation. Avoid breathing mist, gas or vapours. Avoid contacting with skin and eye. Use personal protective equipment. Wear chemical impermeable gloves. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

6.2. Environmental protection measures

Avoid dust formation.

Avoid breathing mist, gas or vapours.

Avoid contacting with skin and eye.

Use personal protective equipment.

Wear chemical impermeable gloves.

Ensure adequate ventilation.

Remove all sources of ignition.

Evacuate personnel to safe areas.

Keep people away from and upwind of spill/leak.

6.3. Methods and material for containment and cleaning up

Collect and arrange disposal.

Keep the chemical in suitable and closed containers for disposal.

Remove all sources of ignition.

Use spark-proof tools and explosion-proof equipment.

Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.

6.4. Reference to other sections:

For disposal suggestions see section 13. For exposure controls / personal protection suggestions see section 8.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Advice on Safety Handling:

Handling in a well ventilated place. Wear suitable protective clothing. Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Use non-sparking tools. Prevent fire caused by electrostatic discharge steam.

7.2. Conditions for safe storage, including any incompatibilities

Store the container tightly closed in a dry, cool and well-ventilated place. Store apart from foodstuff containers or incompatible materials.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure Controls / Personal Protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

Name	CAS No.	Limit value - Eight hours	Limit value - Short term
		mg/m³	mg/m³
Bitumen	8052-42-4	5	10
Dimethyl Ether	115-10-6	766	958
Talc Powder	14807-96-6	1 respirable aerosol	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

Appropriate engineering controls

Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Set up emergency exits and the risk-elimination area.

Eye/face protection

Wear tightly fitting safety goggles with side-shields conforming to EN 166(EU)

Skin protection

Wear fire/flame resistant and impervious clothing. Handle with gloves. Gloves must be inspected prior to use. Wash and dry hands.

Thermal hazards

no data available

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

Tightly fitting goggles

Other protection measures

Protective clothing

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance: Solid

Odour: no data available

Colour: Black

pH (20°C): Not determined

Boiling Point: > 320 °C. Atm. press.:Ca. 101.325 kPa.

Remarks: Atmospheric pressure assumed, not stipulated in citation.; > 500 °C. Atm. press.:Ca. 101.325 kPa. Remarks: For hard bitumen. Atmospheric pressure assumed, not stipulated in citation.

Melting point / Freezing point: 128 °C. Atm. press.:Ca. 101.3 kPa.

Remarks: Atmospheric pressure assumed, not stipulated in citation.

Flash point: > 180 °C. Atm. press.:Ca. 101.325 kPa.

Vapourisation rate: Not determined

Flammable (solid): Not determined

Flammability (gas): Not determined

Ignition temperature: Not determined

Self ignition temperature: 490 °C. Atm. press.:Ca. 101.325 kPa. Remarks:For Asphalt.;430 °C.

Atm. press.:Ca. 101.325 kPa. Remarks: For HFO (Visbreaking Residue).;>= 410 - <= 440 °C. Atm. press.:Ca. 101.325 kPa. Remarks: For Residue (Vacuum Distillation).

Lower explosion limit: Not determined

Upper explosion limit: Not determined

Vapour pressure: < 0.1 kPa. Temperature:Ca. 20 °C.

Relative density: >= 0.925 - <= 1.07. Temperature:15 °C.

Vapour density: Not determined

Solubility in water: Not determined

Solubility/other: Not determined

Partition coefficient n- octanol/water (log P O/W): Not determined

Decomposition temperature: Not determined

Viscosity dynamic: mm2/s (kinematic) = <= 1 382. Temperature:60.0°C.

Remarks: Penetration grade bitumen.;mm2/s (kinematic) = >= 1 981 - ca. 2 552. Temperature:100.0°C. Remarks:Penetration grade bitumen.;mm2/s (kinematic) = >= 0 - <= 3 210. Temperature:135.0°C. Remarks:Hard grade bitumen.

Viscosity kinematic: Not determined

Oxidising properties: Not determined

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information: No further relevant information available

SECTION 10: Stability and Reactivity

- 10.1. Reactivity: No data available
- 10.2. Chemical stability: No data available
- 10.3. Possibility of hazardous reactions: No data available
- 10.4. Conditions to avoid: No data available
- 10.5. Incompatible materials: No data available
- 10.6. Hazardous decomposition products: No data available

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	Rat		
LD50 acute dermal	> 2000 mg/kg	Rabbit		
LC50 acute inhalation	> 94.4 mg/l	Rat		

Skin corrosion/irritation

no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

STOT-single exposure

no data available

STOT-repeated exposure

no data available

Aspiration hazard

no data available

SECTION 12: Ecological Information

12.1. Toxicity

- Toxicity to fish: LL50 Oncorhynchus mykiss (previous name: Salmo gairdneri) > 1 000 mg/L - 96 h.
- Toxicity to daphnia and other aquatic invertebrates: LL50 Daphnia magna > 1 000 mg/L - 48 h.
- Toxicity to algae: EL50 Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) - > 1 000 mg/L - 72 h.
- Toxicity to microorganisms: LL50 Tetrahymena pyriformis > 1 000 mg/L 40 h.
- **12.2. Persistence and degradability:** No information available.
- **12.3. Bioaccumulative potential**: No information available.
- 12.4. Mobility in soil: No information available.
- 12.5. Results of PBT and vPvB assessment: No information available.
- 12.6. Other adverse effects: No information available.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.

Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning.

Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

SECTION 14: Transport Information

14.1. UN number:	1950	1950	
14.2. UN proper shipping name:	AEROSOLS	AEROSOLS	AEROSOLS,
14.3. Transport hazard class(es):	2	2	2.
14.4. Packing group:	-	-	-
14.5. Environmental hazards:	No	No	No
14.6. Special precautions for user			
No information available			

14.7. Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code:

Not applicable

SECTION 15: Additional Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixto	ure
--	-----

Chemical Name	Common	CAS	EC
	names and	number	number
	synonyms		
Asphalt	Bitumen	8052-42-4	232-490-9
Dimethyl ether	Dimethyl ether	115-10-6	204-065-8
Talc	Talc Powder	14807-96-6	238-877-9
(Mg3H2(SiO3)4)			
Petroleum resins	Petroleum	64742-16-1	265-116-8
	resins		
poly(chloroprene)	Chloroprene	9010-98-4	618-463-8
macromolecule			
Solvent naphtha (petroleum),	Solvent	64742-94-5	265-198-5
heavy arom.	Naphtha		
none	Mesitylene2768-	2768-92-5	none
	92-5		

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other Information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
IMDG: International Maritime Dangerous Goods
IATA: International Air Transportation Association
TWA: Time Weighted Average
STEL: Short term exposure limit
LC50: Lethal Concentration 50%
LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

Key literature references and sources for data

IPCS - The International Chemical Safety Cards (ICSC), website:

http://www.ilo.org/dyn/icsc/showcard.home

HSDB - Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm

IARC - International Agency for Research on Cancer, website: http://www.iarc.fr/

eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple

ChemIDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp

ERG - Emergency Response Guidebook by U.S. Department of Transportation, website:

http://www.phmsa.dot.gov/hazmat/library/erg

Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestisstoffdatenbank/

index-2.jsp

ECHA - European Chemicals Agency, website: https://echa.europa.eu/

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU- directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Please note that due to the on-going change in regulation from CHIP to CLP, any MSDS information in this MSDS is only considered accurate at the time of its creation. During this time classifications of substances may change. Therefore it is possible that can art work and MSDS information may differ. As such if you have any concerns we recommend you request a new MSDS from us every 6-12 months.