



INDIVIDUAL SLATE AND TILE SOAKERS

20 YEAR GUARANTEE

The individual soakers range is compatible with a wide range of tiles and slates with both right and left hand options where required.



FEATURES AND BENEFITS

- Quick and simple to install
- Thermally stable
- UV and acid rain resistant
- Lead alternative
- Reduced theft risk
- Creates no harmful run off into water courses
- Dry fix products eliminate the mortar installation and maintenance issues

APPLICATION

A range of lead-free preformed soakers for roof abutment details covering interlocking flat tiles, single lap slate and plain tiles, and double lap plain tiles and slates.












They are supplied preformed to save time and effort on site, and are finished by the use of a lead or lead replacement flashing product.

MATERIAL

Polypropylene

PLEASE SEE
OVERLEAF
FOR
COMPATIBILITY

PRODUCT CODE AND DIMENSIONS

 <p>GREY Interlocking Tiles HD MDS H: 75mm W: 185mm L: 430mm</p>	 <p>BLACK Interlocking Slates HD RCS H: 105mm W: 155mm L: 280mm</p>
 <p>GREY Interlocking Tiles HD RRS H: 75mm W: 180mm L: 430mm</p>	 <p>BLACK Plain Tiles HD PCS H: 75mm W: 100mm L: 170mm</p>
 <p>GREY Interlocking Tiles HD RTS H: 75mm W: 175mm L: 410mm</p>	 <p>BLACK Slates HD SS500 H: 85mm W: 100mm L: 300mm</p>
 <p>GREY Interlocking Tiles HD SRRS H: 75mm W: 180mm L: 430mm</p>	 <p>BLACK Slates HD SS600 H: 85mm W: 100mm L: 380mm</p>
 <p>BLACK Interlocking Plain Tiles HD DTS H: 105mm W: 145mm L: 240mm</p>	<p>  * 100% recycled grey PPC  ** up to 50% recycled PPC </p>

RELATED PRODUCTS

	<p>Universal Abutment Cover Flashing A continuous GRP cover flashing in Anthracite, designed as an effective lead alternative for roof abutments. Code: HD UACF</p>
	<p>Fast Flash An environmentally friendly, lead-alternative flashing. Available in 3 colours of 5 metre rolls in 4 widths, codes: Fast Flash 140, 280, 370, 560</p>
	<p>Tile & Slate Vapour Permeable Roofing Underlays Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180</p>

INDIVIDUAL SOAKER COMPATIBILITY

BMI (REDLAND)	
Cambrian	RCS
Duo Plain	DTS
Landmark Slate 10	RTS
Mini Stonewold	MDS
Richmond	RRS
Richmond 10	RTS
Saxon 10	RTS
Stonewold Mkl	MDS

BREEDON	
Elite	SRRS
Flat	MDS

DOUBLE LAP TILES AND SLATES	
Plain Tiles (All)	PCS
Slates 500mm x 250mm	SS500
Slates 600mm x 300mm	SS600

FORTICRETE	
Gemini	DTS
Minislate	DTS

F P McCANN	
Thin Flat	RTS

MANNOK (QUINN)	
Devenish	RTS
Rathmore	RTS
Western Slate	MDS

MARLEY	
Ashmore	DTS
Duo Modern	MDS
Edgemere	SRRS
Melbourn	RCS
Modern	MDS

RUSSELL	
Bute	SRRS**
Galloway	RTS
Grampian	MDS
Highland	MDS
Lothian	RTS
Moray	RTS
Polden	RTS

WIENERBERGER (SANDTOFT)	
Balmoral	SRRS
Britlock	RCS*
Calderdale Slate	MDS
Cassius	SRRS**
Danum TLE	MDS
Dual Calderdale	MDS
Rivius	SRRS**
TLE	RTS
20/20	SRRS**



* 100% recycled grey PPC
 ** up to 50% recycled PPC

* Subject to minimum rafter pitch of 30° and minimum headlap of 95mm
 ** Longer than the tiles; the length maybe trimmed at the head if required